



Ethernet Switch Ha-VIS sCon 3100-AA

10-port Ethernet Switch for mounting onto top-hat mounting rail in control cabinets, including 2 Gigabit ports and sCon functions, extended temperature range

Unmanaged	IP30	PROFINET compatible <input checked="" type="checkbox"/>	EtherNet/IP compatible <input checked="" type="checkbox"/>
-----------	------	---	--

Number of ports, Copper / Termination 8x 10/100Base-T(X) / RJ45 (Twisted Pair)
 2x 10/100/1000-Base-T(X) / RJ45 (Twisted Pair)

Input voltage / Termination 24 / 48 V DC / 5-pole, pluggable screw contact, for redundant power supply

Permissible range (min./max.) 9.6 V ... 60 V DC

Input current approx. 240 mA (at 24 V DC)

Alarm signalling contact Change-over contact, potential-free, 24 V DC / 0.5 A
 3-pole pluggable screw contact

Housing material metal, powder-coated

Dimensions (W x H x D) 60 x 132 x 104 mm (including cap, without connectors)

weight approx. 0.6 kg

Working temperature -40 °C ... +70 °C


Approvals UL 508; UL 60 950-1; DNV

MTBF 670.000 h

Identification	Part number	Drawing	Dimensions in mm
----------------	-------------	---------	------------------

Ha-VIS sCon 3100-AA
 Ethernet Switch with
 10 RJ45 ports

20 76 110 1001



Ha-VIS sCon