

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

ETO
PCK

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
Δ					Δ				
Δ					Δ				

APPLICABLE STANDARD				STORAGE TEMPERATURE RANGE		-10 °C TO 60 °C <sup>(2)</sup>	
OPERATING TEMPERATURE RANGE		-55 °C TO 85 °C <sup>(1)</sup>		OPERATING HUMIDITY RANGE		40 % TO 80 %	
RATING VOLTAGE		125 V AC		STORAGE HUMIDITY RANGE		40 % TO 70 % <sup>(2)</sup>	
CURRENT		0.5 A					

**SPECIFICATIONS**

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION				
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT. ACCORDING TO DRAWING.		
MARKING		CONFIRMED VISUALLY.		

ELECTRICAL CHARACTERISTICS				
CONTACT RESISTANCE	100 mA (DC OR 1000 HZ).	45 mΩ MAX.	X	
CONTACT RESISTANCE	20 mV MAX, 1 mA(DC OR 1000HZ)	55 mΩ MAX.	X	
MILLIVOLT LEVEL METHOD				
INSULATION RESISTANCE	250 V DC.	100 MΩ MIN.	X	
VOLTAGE PROOF	300 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	

**MECHANICAL CHARACTERISTICS**

MECHANICAL OPERATION				
500 TIMES INSERTIONS AND EXTRactions.				
① CONTACT RESISTANCE: 55 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				
X				
VIBRATION				
FREQUENCY 10 TO 55 Hz. AMPLITUDE : 1.52 mm, AT 2 h FOR 3 DIRECTION.				
① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				
X				
SHOCK				
490 m/s <sup>2</sup> , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				
X				

**ENVIRONMENTAL CHARACTERISTICS**

DAMP HEAT (STEADY STATE)				
EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.				
① CONTACT RESISTANCE: 55 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN.				
X				
RAPID CHANGE OF TEMPERATURE				
TEMPERATURE: -55→+15→+35→+85→+15→+35°C TIME 30 → 10~15 → 30 → 10~15 min				
③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				
X				
CORROSION SALT MIST				
EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				
① CONTACT RESISTANCE: 55 mΩ MAX. ② NO HEAVY CORROSION.				
X				
HYDROGEN SULPHIDE				
EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA-38)				
X				
RESISTANCE TO SOLDERING HEAT				
① SOLDER BATH: SOLDER TEMPERATURE, 260±5°C FOR IMMERSION, DURATION, 10±1s. ② SOLDERING IRONS : 360°C FOR 5 s.				
NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINAL.				
X				
X				
SOLDERABILITY				
SOLDERED AT SOLDER TEMPERATURE 240±3°C FOR IMMERSION DURATION, 2s.				
A NEW UNIFORM COATING OF SOLDER SHALL OVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSSED.				
X				

REMARKS		DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
1) TEMPERATURE RISE INCLUDED WHEN ENERGIZED. 2) THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.		LOKAYAMA	KNAKAMURA	<i>H Okawa</i>	<i>H Okawa</i>	
Unless otherwise specified, refer to MIL-STD-1344.		04.06.11	04.06.11	07.06.14	07.06.14	

Note QT: Qualification Test AT: Assurance Test X: Applicable Test

<b>HRS HIROSE ELECTRIC CO., LTD.</b> SPECIFICATION SHEET PART NO. FX2B-**PA-1. 27DSAL (71)	
CODE NO. (OLD)	DRAWING NO.
CL	ELC4 - 151043-21
CODE NO.	CL 572
FORM No. 231-1	1/1

