

# SLPT Antennas for LTE, WLAN, 3G/4G Applications

## Low Profile Transit Style Antennas

Pulse/Larsen is proud to introduce the SLPT (Shadow Low Profile Transit) product line for Public Safety, WLAN, LTE and 3G/4G applications. These rugged, aesthetically pleasing antennas provide a smaller, slimmer option to our current LPT product line without sacrificing mechanical or electrical performance. The product line includes both NMO and tamper-proof direct mount products, which will support multiple cable and connector options.

SLPT antennas were designed to perform over the high-percentage bandwidth applications prevalent in today's market. As a new product line, these antennas were created specifically to serve emerging applications such as 700 MHz Public Safety, LTE, Smart Grid and WLAN. These value-oriented antennas provide a cost-effective, high-performance solution for LTE and 802.11n MIMO applications as well.

Part Number	Mounting Style	Frequency [MHz]
SLPT698NMO	NMO	698 - 806
SLPT740NMO	NMO	740 - 869
SLPT806NMO	NMO	806 - 960
SLPT2400NMOHF *	NMOHF	2400 - 2485
SLPT4900NMOHF *	NMOHF	4900 - 5900
SLPT698/2170NMOHF *	NMOHF	698-960 / 1710-2500
SLPT2400/5900NMOHF *	NMOHF	2400-2500 / 4900-5900
SLPT698DMN	Direct 3/4" Hole	698 - 806
SLPT740DMN	Direct 3/4" Hole	740 - 869
SLPT806DMN	Direct 3/4" Hole	806 - 960
SLPT2400DMN	Direct 3/4" Hole	2400 - 2485
SLPT4900DMN	Direct 3/4" Hole	4900 - 5900
SLPT698/2170DMN	Direct 3/4" Hole	698-960 / 1710-2500
SLPT2400/5900DMN	Direct 3/4" Hole	2400-2500 / 4900-5900

\* Requires an NMOHF (high frequency) mount

NMO Mount



Direct Mount



# SLPT Antennas for LTE, WLAN, 3G/4G Applications

## Mounting Options



### NMOHF Mounts



SLPT NMO mount (SLPTNMO) antennas are designed to mate perfectly with the Pulse/Larsen NMOHF (high frequency) mount. The NMOHF mount easily converts from low to high frequency applications and back simply by pulling or replacing the center pin and insulator. The larger center contact pin provides for additional strength against downward compression during low frequency installations, resulting in better low frequency VSWR.

For optimal frequency matching, the high frequency and multi band SLPT antennas are designed with an industry-unique coax-type connection which plugs into the Pulse/Larsen NMOHF mount in its high-frequency configuration (i.e. center pin and insulator removed).

NMOHF mounts are available with a variety of cable and connector options. There is also a thick mount version for surface applications up to 1/2" thickness using a standard 3/4" hole. The NMOHF mount is also available in a magnetic mount (NMOMMR) and a mirror bracket (NMOKHFMB).

<p>If your antenna has a "pin" connector, use the NMOHF mount in the low frequency configuration - leave the center pin and insulator in place as it arrives from the factory.</p> <p>"Pin" connector</p> 	<p>If your antenna has a "high frequency" (HF) connector, use the NMOHF mount in the high frequency configuration - remove the center pin and insulator.</p> <p>"HF" connector</p> 
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### NMOHFGPS Mounts

SLPT NMO mount (SLPTNMO) antennas were designed as an ideal match to the NMOHFGPS series mounts. Installing an SLPTNMO antenna on the NMOHFGPS combines the high performance of a GPS antenna with durability of an SLPTNMO antenna. The NMOHFGPS is a direct mount solution utilizing any existing 3/4" hole. This alleviates the need to drill a new hole for mounting.



### Direct Mounts

SLPT direct mount (SLPTDMN) antennas require a 3/4" hole in the mounting surface. SLPTDMN antennas provide a tamper proof solution for applications such as M2M and Public Safety.

**Worldwide Headquarters**  
12220 World Trade Drive  
San Diego, CA 92128  
USA  
Tel 858 674 8100  
Fax 858 674 8262

**Larsen Brand Antennas**  
3611 NE 112th Avenue  
Vancouver, WA 98682  
USA  
Tel 360 944 7551  
800-268 3662 (USA)  
Fax 360 891-0057  
800 525 6749 (USA)

**European Headquarters**  
Pulse GmbH & Co. KG  
Zeppelinstrasse 15  
Herrenberg  
Germany  
Tel +49 7032 7806 0  
Fax +49 7032 7806 12

**Asian Headquarters**  
B402, Shenzhen Academy of  
Aerospace Tech Bldg  
Tech-Innovation Internat'l  
10th Kejianan Road  
High Tech Zone  
Nanshan District, Shenzhen  
PR China  
Tel 86 755 33966678  
Fax 86 755 33966700

**Pulse North Asia**  
3F, No. 198, Zhongyuan Rd  
Zhongli City (32068)  
Taoyuan Hsien  
Taiwan (R.O.C.)  
Tel 886 3 4356768  
Fax 886 3 4356823

**Pulse (Suzhou) Wireless  
Products Co, Ltd**  
#99 Huo Ju Road  
(#29 Bldg, 4th Phase)  
Suzhou New District  
Science & Tech Industrial Park  
Jiangsu Province  
Suzhou 215009 PR China  
Tel 86 512 6807 9998  
Fax 86 512 6809 8023