

APPLICATOR PARTS LIST				TYPE		FLANGED SPADE		AMP INCORPORATED HARRISBURG, PENNA.			
NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	CRIMPING DATA			TERMINALS
1	WIRE CRIMPER	1	7-456406-0	42	Form Tool	1	387603	TO APPLY TERMINAL			42318-A
2	INS. CRIMPER			43							42319-A
3	ANVIL	1	378395	44				WIRE SIZE	CRIMP HEIGHT		
4	ANVIL SPACER			45				20	.067		
5	SHEAR BLADE	1	375746	46				18	.071		
6	REAR SHEAR PLATE	1	377980	47				16	.078		
7	SHEAR BLADE SPACER	2	370494	48				CRIMP SIZE	TYPE	FEED	
8	FRONT SHEAR PLATE	1	387216	49				WIRE .090	F	.620	
9	REAR ANVIL SPACER PLT.	1	372393	50				INSUL.			
10	FRONT ANVIL SPACER PLT.			51				SLEEVED			
11	TOOL SPACER			52				INSULATION RANGE	WIRE RANGE		
12	CRIMP SPACER			53					20-16		
13	FRONT STRIP GUIDE	1	386283-1	54				EXPLODED VIEW			
14	REAR STRIP GUIDE	1	386283-2	55				A-6000 A-6000-1			
15	RAM	1	471911	57				REMARKS:			
16	TOOL HOLDER			58				■ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT THIS APPLICATOR IS TO BE USED ON AMP-O-ELECTRIC 1-471223-3 AMP-O-ELECTRIC 1-471223-3			
17	ADJ. CRIMP MOUNT			59							
18	ADJ. BLOCK			60							
19	APPLICATOR MOUNT ADJ.	1	570656	61							
20	BASE PLATE			62							
21	BASE BLOCK			63							
22	STRIP GUIDE PLATE			64							
23	ANVIL HOLDER	1	370526	65	Tension Adj. Plate	1	374999				
24	AUX. ANVIL HOLDER	1	377515								
25	STRIPPER	1	810872-1	66							
26	STRIPPER MOUNT	1	370660	67							
27	RETAINER PLATE	1	372251	68							
28	STRIPPER MOUNT BRACKET			69							
29	STRIPPER BUSHING			70							
30	STOCK DRAG	1	375381	71							
31	STOCK DRAG HANDLE	1	375382	72	MECH. FEED ASSY						
32	STOCK DRAG STUD 354045-1	2	370523	REV.	REVISION RECORD	DATE	BY	ECN			
33	STOCK DRAG SPRING	2	1-23847-1	A	RETYPED W/ CHANGES	8-5-69	FR	16879	Align Ga. 679597-1		
34	STOCK DRAG ADJ. SCREW	2	372997	B	REV PER ECN	9-5-70	BE	1-773	SERIAL NO.	DATE SHIPPED	DESIGNED
35	FEED FINGER HOLDER			C	REV PER ECN	12-70	BE	1-780			1 KM
36	FEED FINGER	1	375093	D	REV PER ECN	3-7-73	BE	1-9575	CUSTOMER NAME AND ADDRESS		2669
37	FEED FINGER TIP			E	REV PER ECN	11-20-73	BE	2-5078			APP'D
38	FEED FINGER SPACER			F	REV PER ECN A-261970	11-20-73	BE	CS			1-6-66
39	BASE CASTING	1	570238	G	ECN A-395892	9-92	BE	TD	APPLICATOR NUMBER	REV.	SHEET
40	GUARD 457664-2	1	470868						G	672165-1	1 OF 1
41											

OK