



ADVANCED CABLE TIES PART NUMBER	SCREW SIZE	A - WIDTH IN (mm) +/- .005 (.127mm)	B - CLOSED DIAMETER IN (mm) +/- .010 (.254mm)	C - CENTER TO CENTER IN (mm) +/- .050 (1.270mm)	D - OVERALL LENGTH IN (mm) +/- .050 (1.270mm)	E - THICKNESS IN (mm) +/- .005 (.127mm)	ANSI/ UL 94 M1 FLAMABILITY RATING		
AP(R,L)-SAC-125	# 6	.377 (9.575mm)	.082 (2.082mm)	.314 (7.975mm)	.800 (20.320mm)	.046 (1.168mm)	UL 94-V2		
AP(R,L)-SAC-187	# 6	.377 (9.575mm)	.151 (3.835mm)	.362 (9.194mm)	.867 (22.021mm)	.049 (1.244mm)	UL 94-V2		
AP(R,L)-SAC-250	# 6	.396 (10.058mm)	.205 (5.207mm)	.409 (10.388mm)	.900 (22.860mm)	.049 (1.244mm)	UL 94-V2		
AP(R,L)-SAC-312	# 6	.396 (10.058mm)	.256 (6.502mm)	.440 (11.176mm)	.982 (24.942mm)	.049 (1.244mm)	UL 94-V2		
AP(R,L)-SAC-375	# 10	.486 (12.344mm)	.352 (8.940mm)	.492 (12.496mm)	1.117 (28.371mm)	.057 (1.447mm)	UL 94-V2		
AP(R,L)-SAC-500	# 10	.486 (12.344mm)	.470 (11.938mm)	.582 (14.782mm)	1.233 (31.318mm)	.057 (1.447mm)	UL 94-V2		
AP(R,L)-SAC-625	# 10	.486 (12.344mm)	.564 (14.325mm)	.622 (15.798mm)	1.335 (33.909mm)	.060 (1.524mm)	UL 94-V2		
AP(R,L)-SAC-750	# 10	.469 (11.912mm)	.693 (17.602mm)	.708 (17.983mm)	1.460 (37.084mm)	.060 (1.524mm)	UL 94-V2		
AP(R,L)-SAC-875	# 10	.469 (11.912mm)	.813 (20.650mm)	.767 (19.481mm)	1.577 (40.055mm)	.057 (1.447mm)	UL 94-V2		
AP(R,L)-SAC-1000	# 10	.469 (11.912mm)	.890 (22.606mm)	.820 (20.828mm)	1.684 (42.773mm)	.057 (1.447mm)	UL 94-V2		
AP(R,L)-SAC-1250	# 10	.469 (11.912mm)	1.126 (28.600mm)	.940 (23.876mm)	2.000 (50.800mm)	.065 (1.651mm)	UL 94-V2		
AP(R,L)-SAC-1500	# 10	.486 (12.344mm)	1.440 (36.576mm)	.980 (24.892mm)	2.168 (55.067mm)	.060 (1.524mm)	UL 94-V2		
						 ACT ADVANCED CABLE TIES, INC.			
								SELF-ALIGNING CLAMPS	
						COLOR DESIGNATIONS:	MATERIAL:		
						A	6/24/19	DW	FB
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	DW	6/24/19	FB	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
 THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.101.1