

## Terminal markers WS 12/5 FWZ 21-30

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



**WS markers** are the perfect match for the connectors of the W series. But thanks to their system compatibility the WS tags can also be used with the I series and the Z series. The large areas for printing permit not only long character strings but also multiple lines.

**WS markers** are ideal for labels with long, bespoke character strings. The tried-and-tested MultiCard format means that printing can be carried out with **laser** printers, **PrintJet, plotters** or the **MC-Mobilo**.

- Can be fitted in strips or singly
- Markers in proven multicard format

### General ordering data

|            |   |
|------------|---|
| Order No.  | <a href="#">1773330021</a>                                  |
| Type       | WS 12/5 FWZ 21-30   |
| Version    | Terminal markers, Card, 12 x 5 mm, Polyamide, Colour: White |
| GTIN (EAN) | 4032248140886   |
| Qty.       | 300 pc(s).  |

**Terminal markers**  
**WS 12/5 FWZ 21-30**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|            |        |       |      |
|------------|--------|-------|------|
| Length     | 12 mm  | Width | 5 mm |
| Net weight | 0.14 g |       |      |

**Markings**

|  |         |                                   |                                 |
|--|---------|-----------------------------------|---------------------------------|
| Cadmium                                      | No      | Colour                            | White                           |
| Colour of printing                           | Black   | Conductor O.D.                    |                                 |
| Halogen                                      | No      | Material                          | Polyamide                       |
| Material colour according to resistance code | 9       | Operating temperature range, max. | 100 °C                          |
| Operating temperature range, min.            | -40 °C  | Orientation of print              | horizontal                      |
| Pin can be written (STI)                     | Yes     | Pitch in mm (P)                   | 5 mm                            |
| Printed characters                           | Numbers | Printing method                   | Plotter printing with india ink |
| Silicone                                     | No      | UL 94 flammability rating         | V-2                             |

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 2.0   | EC000761    | ETIM 3.0   | EC000761    |
| UNSPSC     | 30-21-18-07 | eClass 4.1 | 24-19-02-19 |
| eClass 5.1 | 27-14-11-37 | eClass 6.2 | 27-14-11-37 |
| eClass 7.1 | 27-14-11-37 |            |             |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|