


			1	
	Part Number:		DRAWN	
	TE101	2803-1	CJ	1/20/2017
	IEIU		CHECKED	1/20/2017
			P.D	
	Description:	nical Transducer	APPROVED	1/20/2017
	Electro-Mecha		J.S	

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


Top View


Side View

Bottom View



Weight





4) Subject to change or redrawn without notice

Items	Specifications	Conditions					
Sound Pressure Level	93	dB (@ 10cm)					
Resonant Frequency	2,830	Hz	REVISION HISTORY				
Rated Voltage	3.6	V	REV	DESCRIPTION	DATE	APPROVED	
Voltage Range	3 ~ 4.5	V		Released from Engineering	8/27/2014	J.S.	
Coil Resistance	18±5	Ω	1	Updated to new template	1/20/2017	J.S.	
Max. Rated Current	100	mA	2	Corrected voltage range and weight	5/18/2017	C.E.	
Storage Temperature	-40 ~ +85	°C	3	Updated operating temperature	3/29/2021	J.S.	
Operating Temperature	-40 ~ +85	°C	NOTES				
Connection Method	Surface Pads			All dimensions are in mm unless otherwise noted			
Mount Type	Surface Mount			2) All tolerances are ± 0.2 mm unless otherwise noted			
Housing Material LCP				3) All parts meet RoHS			