

FB-PS-MB-25DSUB/EX - Power supply unit



2316146

<https://www.phoenixcontact.com/us/products/2316146>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Four-channel, redundant fieldbus power supply base. Host connection is a D-SUB 25 socket connector.



Product description

Universal four-channel, redundant fieldbus power supply base with D-SUB 25 host connector.

Your advantages

- Redundancy
- Built-in relay diagnostics

Commercial data

Item number	2316146
Packing unit	1 pc
Sales key	DN11
Product key	DNC1Z1
Catalog page	Page 459 (C-6-2019)
GTIN	4055626128351
Weight per piece (including packing)	1,078.6 g
Weight per piece (excluding packing)	1,131 g
Customs tariff number	85366990
Country of origin	US

Technical data

Notes

Utilization restriction

CCCex note	Use in potentially explosive areas is not permitted in China.
------------	---

Product properties

Product type	Device coupler
--------------	----------------

Output data

Signal

Output name	Alarm
-------------	-------

Connection data

Supply

Conductor cross section, flexible	0.20 mm ² ... 2.50 mm ²
Conductor cross section, rigid	0.20 mm ² ... 2.50 mm ²
Conductor cross section AWG	30 ... 12

Ex data

Safety data

Inductance Li	17.8 mH (trunk and host)
Max. output voltage U _o	30 V DC (trunk and host)

Interfaces

Data: Invensys DCS cabling system

Number of connections	1
Connection method	D-SUB-25 female connector

Dimensions

Width	180 mm
Height	77 mm
Depth	180 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Max. permissible relative humidity (operation)	95 % (non-condensing)
Permissible humidity (operation)	95 % (non-condensing)

Approvals

Conformity/Approvals

Conformance	CE-compliant
Fieldbus Foundation	FF-831
EN	EN 61326
NE	NAMUR NE 21

Ex data

ATEX	Sira 11ATEX4216X; II 3 G Ex nA nC IIC T4 Gc
IECEX	IECEX SIR 11.0097X; Ex nA nC IIC T4 Gc
CSA, USA/Canada	Class I, Div. 2, Groups A, B, C, D; Ex nA nC IIC T4 Class I, Zone 2, AEx nA nC IIC T4

Standards and regulations

Standards

Standards/regulations	NE21
	EN 61326

Standards/regulations

Standards/regulations	Ring wave noise immunity in acc. with IEC 61000-4-12
-----------------------	--

Standards/regulations

Standards/regulations	Dry heat in acc. with IEC 61131-2
-----------------------	-----------------------------------

Standards/regulations

Standards/regulations	Damp heat in acc. with IEC 61131-2
-----------------------	------------------------------------

Standards/regulations

Standards/regulations	Shock and vibration in acc. with EN 61131-2 and EN 50178
Standards/regulations	IEC 61158-2

2316146

<https://www.phoenixcontact.com/us/products/2316146>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2316146>



IECEX

Approval ID: IECEX SIR 11.0097X



CSA

Approval ID: 2431654



CSAus

Approval ID: 2431654



ATEX

Approval ID: Sira 11ATEX4216X



ATEX

Approval ID: Sira 11ATEX4216X

cCSAus

FB-PS-MB-25DSUB/EX - Power supply unit



2316146

<https://www.phoenixcontact.com/us/products/2316146>

Classifications

ECLASS

ECLASS-11.0	27242692
ECLASS-12.0	27242692
ECLASS-13.0	27242692

ETIM

ETIM 8.0	EC002584
----------	----------

UNSPSC

UNSPSC 21.0	32151600
-------------	----------

FB-PS-MB-25DSUB/EX - Power supply unit



2316146

<https://www.phoenixcontact.com/us/products/2316146>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com