



(B)

- NOTES:
1. MATERIAL: AS NOTED
 2. FINISH: AS NOTED
 3. ELECTRICAL:
VOLTAGE: 600VAC
CURRENT: 25A
 4. TEMP RATING: -20°C TO +90°C
 5. CSA CERTIFIED FILE: LR6837
 6. UL RECOGNIZED FILE: E46237
 7. ALL DIMS ARE FOR REFERENCE UNLESS TOLERANCED OR NOTED OTHERWISE

MATERIAL NO.	ENGINEERING NO.	CHAIN LENGTH
1300190003	22803	1 FT. (0.31 M)
1300190004	22804	2 FT. (0.61 M)
1300190005	22805	3 FT. (0.91 M)

ITEM	DESCRIPTION	MATERIAL	FINISH
5	CHAIN	STEEL	ZINC PLATE
4	YOKE	STEEL	ZINC PLATE
3	#10 X 1/2 RD HD DRIVE SCREW	STEEL	ZINC PLATE
2	SPACER TUBE	CRS	
1	SHORTING PLUG ASSEMBLY	Cu ALLOY (PIN)	YELLOW

FUNCTIONAL SYMBOLS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: ADDED NOTES		molex	
FA = 0	INCH/MM	SCALE	1:1	EC NO: 711366			
FE = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)			DRWN: VHANDI 2021/12/22		DIE BLOCK SHORTING PLUG ASSEMBLY 2 POLE, FEMALE	
FD = 0	4 PLACES	MM	INCH	CHK'D: RSTONE 2022/06/21			
DIVISIONAL SYMBOLS		1 PLACE		APPR: BWOODMAN 2022/06/24		PRODUCT CUSTOMER DRAWING	
		3 PLACES		INITIAL REVISION:		DOCUMENT NUMBER	
		2 PLACES		DRWN: RSTONE 2013/01/15		SD-130019-002	
		0 PLACES		APPR: JFMURPHY 2013/03/01		PSD 001 B	
		ANGULAR TOL ± °		THIRD ANGLE PROJECTION		SHEET NUMBER	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		DRAWING B-SIZE		SERIES 130019	
				MATERIAL NUMBER		CUSTOMER	
				SEE TABLE		GENERAL MARKET	
						1 OF 1	