


BZX85C 3V3 - 33 Series 1.3 Watt Zeners

Absolute Maximum Ratings*

TA = 25°C unless otherwise noted

Tolerance: C = 5%

Parameter	Value	Units
Storage Temperature Range	-65 to +200	°C
Maximum Junction Operating Temperature	+ 200	°C
Lead Temperature (1/16" from case for 10 seconds)	+ 230	°C
Total Device Dissipation	1.3	W
Derate above 25°C	10.4	mW/°C



*These ratings are limiting values above which the serviceability of the diode may be impaired.

NOTES:

- 1) These ratings are based on a maximum junction temperature of 200 degrees C.
- 2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Electrical Characteristics

TA = 25°C unless otherwise noted

Device	V _Z (V)	Z _Z (Ω)	@	I _{ZT} (mA)	Z _{ZK} (Ω)	@	I _{ZK} (mA)	V _R (V)	@	I _R (μA)	I _{SURGE} (mA)	I _{ZM} (mA)
BZX85C 3V3	3.3	20		80	400		1.0	1.0		60	1,380	276
BZX85C 3V6	3.6	15		60	500		1.0	1.0		30	1,260	252
BZX85C 3V9	3.9	15		60	500		1.0	1.0		5.0	1,190	234
BZX85C 4V3	4.3	13		50	500		1.0	1.0		3.0	1,070	217
BZX85C 4V7	4.7	13		45	600		1.0	1.5		3.0	970	193
BZX85C 5V1	5.1	10		45	500		1.0	2.0		1.0	890	178
BZX85C 5V6	5.6	7.0		45	400		1.0	2.0		1.0	810	162
BZX85C 6V2	6.2	4.0		35	300		1.0	3.0		1.0	730	146
BZX85C 6V8	6.8	3.5		35	300		1.0	4.0		1.0	660	133
BZX85C 7V5	7.5	3.0		35	200		1.0	4.5		1.0	605	121
BZX85C 8V2	8.2	5.0		25	200		0.5	5.0		1.0	550	110
BZX85C 9V1	9.1	5.0		25	200		0.5	6.5		1.0	500	100
BZX85C 10	10	7.0		25	200		0.5	7.0		0.5	454	91
BZX85C 11	11	8.0		20	300		0.5	7.7		0.5	414	83
BZX85C 12	12	9.0		20	350		0.5	8.4		0.5	380	76
BZX85C 13	13	10		20	400		0.5	9.1		0.5	344	69
BZX85C 15	15	15		15	500		0.5	10.5		0.5	304	61
BZX85C 16	16	15		15	500		0.5	11		0.5	285	57
BZX85C 18	18	20		15	500		0.5	12.5		0.5	250	50
BZX85C 20	20	24		10	600		0.5	14		0.5	225	45
BZX85C 22	22	25		10	600		0.5	15.5		0.5	205	41
BZX85C 24	24	25		10	600		0.5	17		0.5	190	38
BZX85C 27	27	30		8.0	750		0.25	19		0.5	170	34
BZX85C 30	30	30		8.0	1,000		0.25	21		0.5	150	30
BZX85C 33	33	35		8.0	1,200		0.25	23		0.5	135	27

V_F Forward Voltage = 1.2 V Maximum @ I_F = 200 mA for all BZX85 series