

Ratings

Voltage: 600 V
 Temperature: -40~105 °C
 Flammability: VW-1

Conductor

Conductor count: 1
 Gauge: 28 AWG 0.09 mm²
 Material: tinned copper strands
 Strand size: Ø 0.127 mm x 7
 Resistance at 20 °C: 250 Ω /km max



Insulator

Material: Polyphenylene Ether, Modified (mPPE)
 Color: yellow
 Diameter: Ø 0.9 ±0.08 mm
 Nominal thickness: 0.25 mm
 Resistance at 20 °C: 100 MΩ /km min

Wire marking: E339579 UL AWM STYLE 11028 28 AWG 105°C
 600V VW-1 --- cUL AWM I A/B 105°C 600V FT1 TENSILITY

Bend radius

Minimum: 4 times diameter (3.6 mm)



Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY
A	3/2/2021	Initial release	AG <small>Digitally signed by AG Date: 2021.09.23 09:51:23 -0700'</small>		
			Verified:	Phthalate and halogen free	tel 1.541.323.3228 800 877.670.7118
			JD <small>Digitally signed by JD Date: 2021.09.23 11:26:12 -0700'</small>		fax 1.541.323.4202 web tensility.com
			Dimensions are in millimeters.	Description: Wire, hook-up, TS, 28 AWG, UL 11028, 600V, 105C, 0.9 mm, mPPE, yellow	Size: Part number:
			Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm		A 30-01785
					Scale: 30:1
					⊙ ◻
					Sheet 1 of 1

5

4

3

2

1