



- 1 MATERIAL
HOUSING: THERMOPLASTIC POLYESTER, GLASS FILLED, UL94V-0.
POST: COPPER ALLOY
- 2 FINISH
HOUSING: NATURAL
POST, SEE NOTES 14, 15 & 19 FOR PLATING
- 3 ALL POSITION SIZES HAVE THE BACKWALL NOTCHED ON BOTH ENDS AS SHOWN. THE 5 POSITION SIZE HAS SOLID BACKWALLS. POSITION SIZES 6 AND ABOVE HAVE AN INTERRUPTED BACKWALL AT VARIOUS LOCATIONS. (SEE TABLE FOR INTERRUPTION(S) LOCATIONS).
- 4 POST SOLDER TAILS COMPLY WITH AMP SOLDERABILITY SPEC 109-11-2.
- 5 POST WITHSTANDS 13.34N (3 LB) MIN AXIAL FORCE IN EITHER DIRECTION WITHOUT DISLODGING.
- 6 APPLIES AT -A-
- 7 APPLIES WHEN THE HEADER IS STRAIGHT.
- 8 PLASTIC PROJECTIONS PERMITTED IN THIS ZONE.
- 9 COORDINATE DIMENSIONS APPLIES FROM THE CENTER OF THE ACTUAL FEATURE.
- 10 SOLDER SIDE OF BOARD IS SHOWN.
- 11 THE RETENTION TABS PROVIDE A ONE-TIME INTERFERENCE FIT IN THE 1.63 [0.064] DIAMETER BOARD HOLE FOR HEADER ASSEMBLY RETENTION DURING SOLDERING. FOUR TABS PER PEG, TWO PEGS PER HEADER ASSEMBLY.
- 12 UL MARKING MAY NOT APPEAR ON THE 3 POSITION SIZE. CSA MARKING MAY NOT APPEAR ON THE 3 POSITION SIZE.
- 13 POST NO. 2 & 3 OMITTED.
- 14 PLATING: GOLD PLATE AREA, 0.00076 [0.000030] GOLD OR 0.000076 [0.000003] MIN GOLD FLASH OVER 0.00068 [0.000027] PALLADIUM NICKEL, PER TE CONNECTIVITY'S DISCRETION, ALL SIDES, OVER NICKEL UNDERPLATE, 0.00127 [0.000050] MIN, ALL SIDES AND ENTIRE LENGTH OF POST.
- 15 PLATING: BRIGHT TIN/LEAD (9/37) PLATE AREA, 0.00381-0.00889 [0.000150-0.000350] THICK, ALL FOUR SIDES, 3.18 [0.125] MIN FOR -4 THRU -5.
- 16 DIMENSIONS IN BRACKETS ARE IN INCHES.
- 17 EDGE OF POLARIZING LOCK WALL TO BE IN LINE WITH CENTERLINE OF ADJACENT POST WITHIN ±0.13 [0.005].
- 18 NOTCH SHOWN MAY OR MAY NOT APPEAR.
- 19 PLATING: MATTE TIN PLATE AREA, 0.00381-0.00889 [0.000150-0.000350] THICK, ALL FOUR SIDES 3.18 [0.125]. FOR 3--4 THRU 3--5.

14/18	NONE	19.69	.775	5	3-644784-5
14/18	NONE	15.72	.619	4	3-644784-4
14/18	NONE	19.69	.775	5	644784-5
14/18	NONE	15.72	.619	4	644784-4
FINISH	BACKWALL INTERRUPTION (5) BETWEEN POST	L		NO OF POSITIONS	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN	J. HUFFMAN	12-11-95
DIMENSIONS: mm [INCHES]		CHK	R. SWING	12-11-95
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	D. CLARK	12-11-95
0 PLC	± -	NAME		
1 PLC	± -	MTA-156 HEADER ASSEMBLY, POLARIZED LOCK,		
2 PLC	± 0.13 [0.005]	STRAIGHT .045 SQUARE POST, .000030 GOLD PLATED		
3 PLC	± -	W/RETENTION PEGS, POST NO. 2 & 3 OMITTED		
4 PLC	± -	APPLICATION SPEC		
ANGLES	± -	SIZE		
		114-1020		
MATERIAL	1	WEIGHT	A1 00779 C=644784	
FINISH	2	CUSTOMER DRAWING	SCALE	N/A SHEET 1 OF 1 REV G1