



# SBM4045LDC

## ULTRA LOW VF SCHOTTKY BARRIER RECTIFIER

**Voltage**

**45 V**

**Current**

**40 A**

**TO-263 / D<sup>2</sup>PAK**


Unit : inch(mm)

### Features

- Ultra low forward voltage drop, low power loss
- High efficiency operation
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

### Mechanical Data

- Case: TO-263 package
- Terminals: solder plated, solderable per MIL-STD-750, Method 2026
- Weight: 0.049 ounces, 1.38 grams.
- Marking: Part number



### Maximum Ratings And Electrical Characteristics (T<sub>A</sub>=25°C unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNIT
Maximum repetitive peak reverse voltage		V <sub>RRM</sub>	45	V
Maximum rms voltage		V <sub>RMS</sub>	32	V
Maximum dc blocking voltage		V <sub>R</sub>	45	V
Maximum average forward rectified current	per device	I <sub>F(AV)</sub>	40	A
	per diode		20	
Peak forward surge current : 8.3ms single half sine-wave superimposed on rated load per diode		I <sub>FSM</sub>	300	A
Typical junction capacitance (V <sub>R</sub> =4V, f=1MHz)		C <sub>J</sub>	1100	pF
Typical thermal resistance	(Note 1)	R <sub>θJC</sub>	3.5	°C/W
Operating junction temperature range		T <sub>J</sub>	-55 to +150	°C
Storage temperature range		T <sub>STG</sub>	-55 to +150	°C


Note : 1. Mounted on infinite heatsink.




# SBM4045LDC

Electrical Characteristics ( $T_A=25^\circ\text{C}$  unless otherwise noted)


PARAMETER	SYMBOL	TEST CONDITION		MIN.	TYP.	MAX.	UNITS
Breakdown voltage per diode	$V_{BR}$	$I_R=0.5\text{mA}$	$T_J=25^\circ\text{C}$	45	-	-	V
Instantaneous forward voltage per diode	$V_F$	$I_F=1\text{A}$	$T_J=25^\circ\text{C}$	-	0.28	-	V
		$I_F=5\text{A}$		-	0.35	-	
Instantaneous forward voltage per diode	$V_F$	$I_F=20\text{A}$	$T_J=125^\circ\text{C}$	-	0.47	0.51	V
		$I_F=1\text{A}$		-	0.17	-	
Reverse current per diode	$I_R$	$V_R=36\text{V}$	$T_J=25^\circ\text{C}$	-	86	-	$\mu\text{A}$
		$V_R=45\text{V}$	$T_J=125^\circ\text{C}$	-	20	-	$\text{mA}$
Reverse current per diode	$I_R$	$V_R=45\text{V}$	$T_J=25^\circ\text{C}$	-	-	320	$\mu\text{A}$
			$T_J=125^\circ\text{C}$	-	28	-	$\text{mA}$




**Fig.1 Forward Current Derating Curve**



**Fig.2 Typical Junction Capacitance**



**Fig.3 Typical Reverse Characteristics**




**Fig.4 Typical Forward Characteristics**



# SBM4045LDC

## MOUNTING PAD LAYOUT



## ORDER INFORMATION

- Packing information  
T/R – 0.8K per 13" plastic Reel




# SBM4045LDC

PartNo \_packing code \_Version

SBM4045LDC\_R2\_00001

For example :

RB500V-40\_R2\_00001



Packing Code <b>XX</b>				Version Code <b>XXXXX</b>		
Packing type	1 <sup>st</sup> Code	Packing size code	2 <sup>nd</sup> Code	HF or RoHS	1 <sup>st</sup> Code	2 <sup>nd</sup> ~5 <sup>th</sup> Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			



## **SBM4045LDC**

### Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.