



SPECIFICATIONS:

Housing: Thermoplastic, UL-94V-0 rated
 Contacts: Copper alloy
 Electrical ratings: 660W, 600V
 Max. Operating temperature: 120°C
 Applicable Wire type: 18AWG solid copper
 (acceptable for use with cooper clad wire such as AWM style 11125)
 Applicable Panel thickness: 1.0 - 1.5mm
 For T8 bulb type
 For G13 Base
 For Rapid Start (I)

Certifications:
 UL 542
 UL 496
 CSA 22.2 / 43



RoHS
 COMPLIANT

REVISIONS		CHNG	CHK	APPR
REV	DATE	CHANGE	UPDATED DRAWING	PB
A	11/16/17			

TOLERANCE UNLESS OTHERWISE SPECIFIED	
X	± 1
X.X	± 0.4
X.XX	± 0.13
DRAWN BY	PB
CHECK BY	
APPR BY	
DATE:	10/26/17

Power Dynamics, Inc.
 Phone: 973 560-0019 Whippany, New Jersey Fax: 973 560-0076

**PART: FLUORESCENT / LED T8 LAMPHOLDER FOR G13 BASE
 MEDIUM BI-PIN; NON-SHUNTED; TURN TYPE WITH LOCK
 FOR RAPID START**

PD-FL-13

SHEET 1 of 1

SCALE: NTS ALL DIMENSIONS FOR REFERENCE ONLY
 DIMENSIONS ARE IN MILLIMETERS