



PERFORMANCE CHARACTERISTICS

- CURRENT RATING: 1.5 A AT 20°C (FULLY LOADED)
- 1 A AT 70°C (FULLY LOADED)
- RATED VOLTAGE: 500 V AC (CONT /CONT)
- OPERATING TEMPERATURE : -55°C TO 125°C
- CONTACT RESISTANCE : 20 m Ω MAX
- INSERTION FORCE: 0.75N MAX/CONT
- EXTRACTION FORCE : 0.15N MIN /CONT
- INSULATION RESISTANCE: 10<sup>4</sup> MΩ MIN

NOTES 1. HM2R02PA5101 LEAD FREE INDICATOR : LF=LEAD FREE(DIGIT 15&16)  
PLATING CODE(DIGIT 13&14)

Plating code	Plating	Performance Level
AA	0.75µm Au	IEC performance level 2(250mating cycles)orTELCORDIA C0
AB	1.25µm Au	TELCORDIA UE

- THIS PRODUCT IS CSA APPROVED.  
THIS PRODUCT IS UL RECOGNIZED.
- FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING :BS.A.201572.001
- THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

Material		Spec ref	
Mat code		✓	TOLERANCE
Heatreat			1DEC ±0.2 1DEC 2DEC ±0.1 2DEC
Plating/Finish			ANGLES ±1°HDEKEN
Dr	Nickor Zuo	Jul-20-09	size
Eng	Nickor Zuo	Jul-20-09	Scale
Chr	PeiMing Zheng	Jul-20-09	A1
Appr	Joseph Hsia	Jul-20-09	5.000
Product family		ECN	
Model Name		REL Level	
Model Revision		BSC201418032	
Pro/E file	CAT.NO. HM2R02PA5101----	CUSTOMER DRAWING	sheet 1 of 1

This drawing is the property of FCI. It is to be used for manufacturing purposes only. All rights reserved. FCI, the FCI logo, and the FCI symbol are trademarks of FCI. Copyright © 2011.