



SIMATIC DP, Electronic module for ET 200 PRO 4 AI U High Feature, +-10 V; 0...10 V; +5 V; 1...5V; Channel diagnostics; incl. bus module, Connection module IO 6ES7194-4..00-0AA0 order separately

Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes; against destruction
Input current	
from supply voltage 1L+, max.	40 mA; Typical
from backplane bus 3.3 V DC, max.	12 mA; Typical
Encoder supply	
Number of outputs	4
Short-circuit protection	Yes; per module, electronic to frame
Output current	
<ul style="list-style-type: none"> up to 55 °C, max. 	1 A
Power loss	
Power loss, typ.	1.1 W
Address area	
Address space per module	<ul style="list-style-type: none"> Address space per module, max.
	8 byte
Analog inputs	
Number of analog inputs	4
permissible input voltage for voltage input (destruction limit), max.	35 V
Cycle time (all channels) max.	5 ms
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> 0 to +10 V 1 V to 5 V -10 V to +10 V -5 V to +5 V 	<ul style="list-style-type: none"> Yes Yes Yes Yes
Cable length	
<ul style="list-style-type: none"> shielded, max. 	30 m
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> Resolution with overrange (bit including sign), max. Integration time (ms) Interference voltage suppression for interference frequency f1 in Hz Conversion time (per channel) 	<ul style="list-style-type: none"> 15 bit; 15 bit + sign at ±10 V, at ±5 V; 15 bit at 0 V to 10 V, at 1 V to 5 V 0,3 / 16,7 / 20 / 60 16,67 / 50 / 60 / 3 600 1.1 ms
Smoothing of measured values	
<ul style="list-style-type: none"> parameterizable Step: None 	<ul style="list-style-type: none"> Yes Yes; 1x cycle time

<ul style="list-style-type: none"> • Step: low 	Yes; 4x cycle time
<ul style="list-style-type: none"> • Step: Medium 	Yes; 16x cycle time
<ul style="list-style-type: none"> • Step: High 	Yes; 64x cycle time
Encoder	
Connection of signal encoders	
<ul style="list-style-type: none"> • for voltage measurement 	Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.0075 %
Temperature error (relative to input range), (+/-)	0.00075 %/K
Crosstalk between the inputs, min.	-70 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.004 %
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> • Voltage, relative to input range, (+/-) 	0.1 %
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Voltage, relative to input range, (+/-) 	0.075 %
Interference voltage suppression for $f = n \times (f1 \pm 0.5 \%)$, $f1 =$ interference frequency	
<ul style="list-style-type: none"> • Series mode interference (peak value of interference < rated value of input range), min. 	60 dB
<ul style="list-style-type: none"> • Common mode interference (USS < 2.5 V), min. 	80 dB; Interference voltage < 10 V
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	Yes; Parameterizable
<ul style="list-style-type: none"> • Hardware interrupt 	Yes; (limit value alarm), can be parameterized for channel 0
Diagnoses	
<ul style="list-style-type: none"> • Diagnostic information readable 	Yes
<ul style="list-style-type: none"> • Wire-break 	Yes; at 1 to 5 V
<ul style="list-style-type: none"> • Short-circuit 	Yes; at 1 to 5 V
Diagnostics indication LED	
<ul style="list-style-type: none"> • Group error SF (red) 	Yes
Potential separation	
Potential separation analog inputs	
<ul style="list-style-type: none"> • between the channels 	No
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes
Permissible potential difference	
Between the inputs and MANA (UCM)	10 Vpp AC
Isolation	
Isolation tested with	707 V DC (type test)
Dimensions	
Width	45 mm
Height	130 mm
Depth	35 mm
Weights	
Weight, approx.	150 g
last modified:	12/19/2020 