



SEE NOTE 7

- NOTES: (b)
- FOR WAVESOLDERING (SOLDER BATH TEMPERATURE 260°C FOR 5SEC. AND SOLDER PREHEAT 100°C FOR 30SEC.)
 - METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
 - INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0; BLACK
 - CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):
 - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
 - PLEASE ADD B for 20µm HARD GOLD over min. 50µm NICKEL
 - PLEASE ADD C for 30µm HARD GOLD over min. 50µm NICKEL
 - CAPACITANCE: 370pF ± 20%
 - DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC
 - CONNECTOR IS PART MARKED: 241□10030X CONEC ABC

Directive 2002/95/EC RoHS compliant

| | | | | | | | | |
|--|--|--------------------------------------|--|---------------------------|--|---------------------|---------------------|--|
| THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND | | | | tolerance | | dim. in mm | scale: 2:1 (5:1) | |
| | | | | date | | | material: SEE NOTES | |
| | | | | name | | title: | | |
| | | | | drawn 07.05.2014 Heinrich | | D-SUB C-FILTER MALE | | |
| appd. 07.05.2014 Henneboel | | 25pos. SOLDER PIN STRAIGHT | | | | | | |
| norm | | dwg no: | | | | | | |
| d-old | | 24K1A279 | | | | | | |
| 3 x b A5200 07.05.2014 Heinrich | | part no: (b) 241□10030X (see note 4) | | | | | | |
| a Original | | DIN-A3 | | | | | | |
| rev. description date name | | sh: 1 | | | | | | |

