

## Corrugated tube screw connection - HC-B-GCA-M20-PLRBK - 1412021

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



EVO corrugated pipe screw connection, size: M20, protection class: IP66, plastic



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Weight per Piece (excluding packing) | 40.0 g   |
| Custom tariff number                 | 39269097 |
| Country of origin                    | Poland   |

### Technical data

#### General

|                       |   |
|-----------------------|---|
| Assembly instructions | Please observe the installation note provided for the WP-PA HF-HB....BK corrugated pipe |
|-----------------------|---|

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 115 °C |
| Degree of protection            | IP66              |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27261207 |
| eCl@ss 8.0 | 27449290 |
| eCl@ss 9.0 | 27440290 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000441 |
|----------|----------|

# Corrugated tube screw connection - HC-B-GCA-M20-PLRBK - 1412021

## Classifications

ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC000441 |
|----------|----------|

## Approvals

Approvals

---

Approvals

EAC

---

Ex Approvals

---

Approvals submitted


---

## Approval details

|     |
|-----|
| EAC |
|-----|

## Drawings

Dimensional drawing



Dimensional drawing

---