

# TW5340/ TW5341

## TW5340/TW5341 Multi-Constellation Smart Antenna

### Overview

The TW5340 is a multi-constellation GNSS Smart Antenna which provides simultaneous GPS/GLONASS/SBAS reception. It is designed for use in professional grade applications such as precision timing, network synchronization, low current applications, and tracking/positioning applications.

The TW5340 GNSS Smart Antenna uses the state-of-the-art ST STA8088 receiver which provides 32 high sensitivity tracking channels plus 2 fast acquisition channels which can be assigned to acquire and track GPS, GLONASS, QZSS, and SBAS (WAAS, EGNOS, MSAS) signals simultaneously.

The TW5340 employs Tallyman's Accutenna™ dual feed antenna patch technology which greatly improves rejection of multi-path signal interference, across the whole GNSS band, making the TW5340 the most precise smart antenna in its size across all operating environments.

The TW5340 accelerates GPS positioning by predicting satellite ephemeris data based on previous observations, resulting in extremely fast Time-To-First-Fix.

The TW5340 can be configured to outputs up to three NMEA 0183 message lists with navigation update rates up to 10Hz. RS232, and CMOS interfaces are available with input voltage options of 3.3V, 5.0V and 12V to 36V with over voltage protection.

A standard one pulse-per-second 1PPS synchronized to UTC time is available as a single ended output or as a differential output at RS422 levels. NMEA data can also be configured to output at RS422 levels, however the 1PPS output is disabled in this mode.



Tallyman's Windows™ based Configurator enables simple configuration of parameters such as baud rates, output message rates, constellation, tracking parameters, 1PPS configuration and Standby mode parameters.

A non-magnetic version is available with Part Number TW5341.

### Features

- Multi-Constellation Receiver/Antenna
- 32 Channel simultaneous operation
- High performance tracking (-162 dBm)
- WAAS, EGNOS, & MSAS enabled
- 3 NMEA 0183 output Lists
- Navigation rates 1 to 10 Hz

- 1 PPS & NMEA configurable RS422 outputs
- Low Current Standby Mode
- Accutenna™ Technology
- Excellent multi-path signal rejection
- Industrial grade IP69K enclosure
- RoHS, REACH and RED Compliant. CE Marking

# TW5340/TW5341 Multi-Constellation Smart Antenna

## Specifications

Antenna		Environmental	
Architecture	Dual Feed	Operating Temperature	-40°C to +85°C
Axial Ratio	<1 dB typical.	Storage Temperature	-45°C to +85°C
Frequencies	GPS / GLONASS / QZSS	Weatherproof	IP69K
SBAS	WAAS, EGNOS, MSAS	Shock	Vertical axis 50G, other axis 30G 3 axis sweep – 15 min 10-200 Hz log sweep 3G
Channels	32 simultaneous plus 2 fast acquisition	Vibration	EN 55022
Navigation Accuracy		Emissions	EN 61000-4-3, EN 61000-4-4, EN
GPS+GLONASS	1.5m (50% CEP)	Immunity	61000-4-6
Interface		Sensitivity	
Outputs	RS232, CMOS	Acquisition	-146 dBm
1 PPS Output	Single ended & Differential RS422. +/-50 ns Accuracy 16kV protection RS422 lines	Tracking	-162 dBm
Mechanical		Time to First Fix	
Dimensions	66.5 mm dia x 21 mm H	Cold start	35 sec
Weight	135 g	Warm start	30 sec
Mounting Method	19 mm dia. (3/4") thru-hole or mast mount	Hot start	<2 sec
Cable Length	5m (15m & 25m special order)	Reacquisition	<1 sec
Connector	RJ45		
Enclosure	Industrial grade magnetic mount weatherproof IP69K		
Electrical		Serial Protocol	
Voltages	3.3V, 5V (+/- 0.5V) and 12 V to 36V (9V min)	Output	NMEA 0183
Current	120 mA during acquisition 80 mA operating Standby mode < 1mA	Baud Rate	300 to 921,600 bps, 115200 (default)
		Update Rate	Configurable up to 10Hz
		NMEA Message	Configurable
Wires			
		Power, Gnd, Rx Tx, 1 PPS Qualification, Differential 1 PPS-A, Differential 1 PPS-B	

## Ordering Information:

33-5340-x-yy-zz GPS/GLONASS /QZSS Smart Antenna, 33-5341-x-yy-zz Non-magnetic, GPS/GLONASS/ Smart Antenna

**DB9 Test adaptor (For CMOS versions a CMOS/RS232 converter will also be required)**

**27-0045-1**

Please refer to the Ordering Guide for the current and complete list of available products.



**TALLYMATICS®**

The **connection** of things.®

Tallymatics manufactures high performance, telematics products and solutions for a wide range of applications. With support for both RF wireless and data networks, Tallymatics enables high-resolution location awareness of mobile field assets across any type of wireless network. Tallymatics is a division of Tallysman.

© 2019 Tallymatics Inc. All rights reserved. Tallymatics, "The connection of things" tag line and the Tallymatics logo are trademarks or registered trademarks of Tallymatics Inc. and/or its affiliates in Canada and certain other countries. All other trademarks mentioned in this document are the property of their respective owners. The information presented is subject to change without notice. Tallysman assumes no responsibility for any errors or omissions in this document. Tallymatics is a division of Tallysman Inc. Tallymatics hereby disclaims any or all warranties and liabilities of any kind.

**Contact us:**

[info@tallymatics.com](mailto:info@tallymatics.com)

T: +1 613 591-3131

Tallymatics Inc.  
36 Steacie Drive,  
Ottawa ON  
K2K 2A9 Canada

[www.tallymatics.com](http://www.tallymatics.com)