
т	۵	н <b>т</b>		0







Keying Shown as example

Connector dimension

Nominal

Dim

## CHARACTERISTICS

ω

-Standard : Based on MIL-DTL-38999 Series III

	Standard . Dasca on r										
$\frown$		: Aluminium				Р	3.25±0.2				
						PP	4.93±0.2				SOURIAU
	-Shell Plating	: Nickel				R1	23.01				due to a
	-Insulator	: Thermoplastic				R2	20.62				the Specifica
	-Contacts	: Copper Alloy				S	28.6±0.3				(pro
	-Seals & Grommet	: Silicon Elastomer				V W	20.83+0/-1.25				
N						Z	2.1/2.5 31.5 Max				
	-Contact Plating	: Gold over copper Alloy 0.8µ	m minimum			VV THREAD	M18x1-6g		Г		
	-Durability	: 500 Mating cycles				VV HINLAD	WIIOXI-0g	]			
	-Delivered without So	uriau contacts									
	-Temperature Range	-65°C to +200°C									
	-Salt Spray	: 48 hours							A	14-10-2016	5 First Release
	-Mass	: 14.72 g ± 10%							ISS	DATE	Latest modif
									Design	ed By:	
										TITLE	
	BASIC SERIES:	8D 0 -	13 F	26	ΡE	L			SCA	ALE	
_	SHELL TYPE : Square	Flange Receptacle					Delivered W/	O Contacts	N	A	$\forall \Psi$
	CONTACT TYPE : Sta							ITATION : E			
	CONTACT TIFE . 318		_   _				UNILI	TATION . L	SO	URIAU	WW
	SHELL SIZE : 13					C	ONTACT TYPE : PIN(50	0 Matings)			
	PLATING : F =	Nickel					CONTACT LAYO	OUT : 13-26	FORM	MAT	-1
									A	3	
L	Н	G			F		E	1	D		С
							$\vee$				

O		Φ		A		_	
						4	
LAY	YOUT SHOWN AS EXA	MPLE				3	
due to a use the Specifications (profession	not be liable for any r of the Products whic issued by either of t onal recommendatio Country FR N: 8D013F2	h does not o he Parties o n, technical Juri	comply with r by a third party	List		2	
						-	
First Release Latest modificatio	on - by				MOD N°		
Date:			CUSTOMER D	RAWING			
	Aluminium	Recepta	cle 8D series	5			
$\exists \bigoplus$	General linear Tolerances: ±		NPRDS / PF 859			1	
WWW.SOURIAU.COM This document is the property of SOURIAU   it must not be reproduced or communicated without permission							
SOURIAU DRG N°   SHEET     8D013F26PEL-C   1/2							
С		B		A		J	

-	т	۵	<u>п</u>	m	D	0
		Contact Layout				Panel Cutou
4		26			Â	SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING
_		2#12 6#22D	1		¥ ∞ –	
ω	Ctc A B C D E F 1 2	X Y   0 3.47   2.47 4.34   2.47 -4.34   0 -3.47   -2.47 -4.34   -2.47 -4.34   3.25 0   -3.25 0				Dim ØA ØA R1 ØT
						SOURIAU shall not be liable for any due to a use of the Products wh the Specifications issued by either of (professional recommendati
N						PN: 8D013F
					A 14-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
					SCALE	Aluminium General linear Tolerances:
-					SOURIA	U WWW.SOURIAU.C
				E T	FORMAT A3	SOURIAU 8D013F2
	Н	G	F F	E	D	C

