



Mallory Sonalert Products, Inc.

Part #:

SCE048LD2MG7B

Sales Outline Drawing

Revision:

C

Specifications:

| | | | | |
|------------------------|--|----------------------------|--|--|
| Sound Level Category: | Loud | Loud | | |
| Mode of Operation: | Continuous | Ding Dong 2.0 - 1.6 kHz | | |
| Pulse Rate (PPS): | N/A | 1.2 | | |
| Loudness @ 2 FT: | 85 to 95 dB(A) Typ. | 85 to 95 dB(A) Typ. | | |
| Frequency: | 2000 ± 500 Hz | 2000 ± 500 Hz | | |
| Connection: | T-BLOCK ONLY | T-BLOCK; BLACK WIRE TO (-) | | |
| Voltage Rating: | 28 to 48 VDC | | | |
| Current Draw: | 40mA MAX | | | |
| Housing Material: | 6/6 Nylon, Color: Black | | | |
| Storage Temperature: | -40° to +85° C | | | |
| Operating Temperature: | -40° to +85° C | | | |
| Panel Mounting: | Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. | | | |
| Knurled Nut: | Used to attach part to panel. The max recommended torque is 10 in-lbs. | | | |
| Weight (Typical): | 2.1 oz (60g) | | | |
| NEMA 3R,4X, & 12: | Approved with use of ACC03. | | | |
| cUL Recognition: | Supply voltage shall employ Transient Voltage Surge Suppression. | | | |
| Options: | Please contact factory. | | | |

Dimensions: Inches (mm)

ROHS Compliant

