

VIEW ON MATING SIDE

∞	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
∞	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A

A = 32 CONTACTS L-2,9

Marking	Standard
Performance level	G2/0 = Contact area level2 / Termination tin
Flux proof	no
Fixing clip	no
Dimensions	SDA-85040-0001 sht.1
Technical Data	PS-85042-0001

A	G2/0	α2,4,6...32	b2,4,6...32
Contact symbol	Perform. level	Contact position number	

ECN 2264 Produkt spec. 96-10-18 KN	REVISIONS		FOR PREVIOUS REVISIONS SEE MRI LIST	
	LTR	Δ-1		
UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 2° INCH METRIC	DRWG BY	SIGN	CAD/CAM PROJECT NAME	SH. REV.
3 PLACE ± . 2 PLACE ± . 1 PLACE ± .	Ca	Ca	s8504006 s91	THIS DRAWING CONTAINS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	CHK'D BY	CHK'D BY	TITLE	
DESIGN DIMENSION <input type="checkbox"/> MM <input type="checkbox"/> IN.	KN	KN	64 pos. female connector acc. DIN 41612 style B contacts arrangement	
EQUIVALENT DIMENSION <input type="checkbox"/> MM <input type="checkbox"/> IN.	APPD BY	APPD BY	MOLEX® MOLEX EUROPE	SHEET NO. DATE 1 OF 1 96/05/15
IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY	SCALE	SCALE	PART NO.	SIZE
			85040-0696	A
			SDA-85040-0696	