

## 4-Outlet Power Strip, 10 ft. (3.05 m) Cord, NEMA 5-15P Plug, 12 in.

MODEL NUMBER: **PS120410**



Metal 12 in. power strip distributes power to multiple devices in an industrial, office, retail, rackmount, raceway, workbench or point-of-sale setting.

### Features

#### Ideal Power Distribution

- Recommended for industrial, office, retail, rackmount, raceway, workbench and point-of-sale settings
- 4 NEMA 5-15R outlets with 1.77 in. center-to-center spacing
- 10-ft. (3.05 m) power cord with NEMA 5-15P plug
- Meets UL1363 (USA) and cUL (Canada) certifications

#### Premium Safety Features

- 15A resettable circuit breaker prevents dangerous overloads
- Transparent switch cover eliminates accidental shutdowns
- Lighted on/off switch confirms operation at a glance

#### Rugged All-Metal Housing

- 12 in. length
- Hardware included for mounting on a wall, floor, workbench or under a counter

## Specifications

| OVERVIEW                           |              |
|------------------------------------|--------------|
| UPC Code                           | 037332198525 |
| INPUT                              |              |
| Nominal Input Voltage(s) Supported | 120V AC      |

### Highlights

- 4 NEMA 5-15R outlets with 1.77 in. center-to-center spacing
- 15A resettable circuit breaker
- Lighted on/off switch with transparent safety cover
- Heavy-duty all-metal housing
- 10-ft. (3.05 m) power cord with NEMA 5-15P plug

### Package Includes

- PS120410 4-Outlet Power Strip, 10-ft. (3.05 m) Cord, 12 in.
- Mounting hardware
- Owner's manual

|  |   |
|--|---|
| Recommended Electrical Service               | 15A 120V  |
| Input Cord Gauge Type                        | 14 gauge; SJT   |
| Voltage Compatibility (VAC)                  | 120   |
| Input Plug Type                              | NEMA 5-15P  |
| Input Cord Length (ft.)                      | 10  |
| Right-Angle Plug                             | No  |
| Input Cord Length (m)                        | 3.05  |
| Integrated Cord Clip                         | No  |
| <b>OUTPUT</b>                                |   |
| Frequency Compatibility                      | 50 / 60 Hz  |
| Output Receptacles                           | (4) 5-15R   |
| Circuit Breaker (amps)                       | 15  |
| Transformer Accommodation                    | (2) Yes   |
| Right-Angle Outlets                          | No  |
| Outlet Spacing                               | 1.77in.   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Switches                                     | Lighted 2 position switch controls power to all outlets   |
| Locking Switch Cover                         | Transparent on/off switch cover prevents accidental turn-off  |
| <b>PHYSICAL</b>                              |   |
| Color  | Silver  |
| Material of Construction                     | Aluminum  |
| Power Cord Color                             | Black   |
| Form Factors Supported                       | Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications |
| Housing Color                                | Silver  |
| Included Mounting Accessories                | Includes mounting clips   |
| Mounting Holes or Slots                      | No  |
| Outlets Measurement (Center to Center)       | 1.77 in.  |
| Receptacle Color                             | Black   |
| Shipping Dimensions (hwd / in.)              | 2.40 x 4.80 x 15.40   |
| Shipping Dimensions (hwd / cm)               | 6.10 x 12.19 x 39.12  |
| Shipping Weight (lbs.)                       | 2.10  |
| Shipping Weight (kg)                         | 0.95  |
| Unit Dimensions (hwd / in.)                  | 1.250 x 1.620 x 12.000  |

|                                      |                                |
|--------------------------------------|--------------------------------|
| Unit Dimensions (hwd / cm)           | 3.18 x 4.12 x 30.48            |
| Unit Weight (lbs.)                   | 1.28                           |
| Unit Weight (kg)                     | 0.58                           |
| Outlet Spacing                       | 1.77 in.                       |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                |
| Antimicrobial                        | No                             |
| Built-In Circuit Breaker             | Yes                            |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                |
| Product Certifications               | cUL Listed; UL 1363; UL Listed |
| Product Compliance                   | RoHS                           |
| <b>WARRANTY &amp; SUPPORT</b>        |                                |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty      |