

SACB-10X0,34/2X0,75-200 PUR - Sensor/actuator cable



1424178

<https://www.phoenixcontact.com/pc/products/1424178>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, application: Distributor boxes, PUR/PVC, cable length: 200 m, shielding: no

Commercial data

Item number	1424178
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BF3ZBX
GTIN	4055626368948
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85444995
Country of origin	DE

SACB-10X0,34/2X0,75-200 PUR - Sensor/actuator cable

1424178

<https://www.phoenixcontact.com/pc/products/1424178>

Technical data


Product properties

Product type	Cable by the meter
Application	Distributor boxes

Cable/line

Cable length	200 m
--------------	-------

PUR/PVC black [PUR]

Dimensional drawing	
Cable weight	111.1 kg/km
UL AWM Style	20549
Number of positions	12
Shielded	no
Cable type	PUR/PVC black [PUR]
Conductor structure signal line	19x 0.15 mm
AWG signal line	22
Conductor cross section	10x 0.34 mm ² (Signal line) 2x 0.75 mm ² (power line)
Wire diameter incl. insulation	1.3 mm ±0.1 mm (Signal line) 1.8 mm ±0.1 mm (power line)
External cable diameter	8.6 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, blue, white, green, yellow, gray, pink, red, black, violet, white/pink, pink/brown
Inner sheath thickness	≥ 0.15 mm
Thickness, outer sheath	≥ 0.38 mm
Overall twist	Wires twisted in layers
Nominal voltage, cable	300 V
Test voltage	2000 V
Minimum bending radius, fixed installation	7.5 x D
Minimum bending radius, flexible installation	10 x D
Max. bending cycles	1500000

SACB-10X0,34/2X0,75-200 PUR - Sensor/actuator cable



1424178

<https://www.phoenixcontact.com/pc/products/1424178>

Flame resistance	DIN EN 50265
Resistance to oil	according to VDE 0472 Part 803
Other resistance	Highly resistant to acids, alkaline solutions and solvents
Special properties	Silicone-free
Ambient temperature (operation)	-40 °C ... 90 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)
	80 °C (in acc. with UL)

SACB-10X0,34/2X0,75-200 PUR - Sensor/actuator cable



1424178

<https://www.phoenixcontact.com/pc/products/1424178>

Classifications

ECLASS

ECLASS-11.0

27060106

ETIM

ETIM 8.0

EC003250

UNSPSC

UNSPSC 21.0

26121600

SACB-10X0,34/2X0,75-200 PUR - Sensor/actuator cable



1424178

<https://www.phoenixcontact.com/pc/products/1424178>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com