

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	11MAY2015	DW	CW
	A1	ECR-17-018349	14DEC2017	DW	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:  
 CONTACT MATERIAL: BRASS  
 SURFACE PLATING:  
 SILVER PLATING:  $\geq 2\mu\text{m}$   
 CONTACT RESISTANCE:  $\leq 0.5\text{m}\Omega$   
 WIRE RANGE:  $50\text{mm}^2$   
 OPERATION TEMPERATURE:  $-40\sim+125^\circ\text{C}$

注释:

1. 技术参数:  
 公针材料: 黄铜  
 表面电镀:  
 镀银:  $\geq 2\mu\text{m}$   
 接触电阻:  $\leq 0.5\text{m}\Omega$   
 接线范围:  $50\text{mm}^2$   
 工作温度:  $-40\sim+125^\circ\text{C}$

T2060001050-000	CHM-50	CHM-50, SILVER PLATING HMN-001公针 $50\text{mm}^2$ , 镀银	50	22.5
PART NUMBER 料号	PART DESCRIPTION 描述		WIRE GAUGE ( $\text{mm}^2$ ) 线规 ( $\text{mm}^2$ )	STRIPPING LENGTH (mm) 剥线长度 (mm)
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 11MAY2015 David Wang		
DIMENSIONS: mm		CHK 11MAY2015 Chris Wang		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 11MAY2015 Xiang Xu	NAME CHM-50 HM PIN CONTACT	
0 PLC $\pm$		PRODUCT SPEC 108-137057	SIZE	
1 PLC $\pm$		APPLICATION SPEC 114-137057	CAGE CODE	
2 PLC $\pm$		WEIGHT	DRAWING NO	
3 PLC $\pm$		Customer Drawing	RESTRICTED TO	
4 PLC $\pm$			A300779	
ANGLES $\pm$			C-T2060001050000	
FINISH			SCALE	
-			2:1	
-			SHEET	
			1 OF 1	
			REV	
			A1	

1470-19 (3/13)