

Specification Sheet

Part Number: 157-00180



Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation

Initial fir tree serves as a locating feature for assistance in blind assembly applications

Disc feature provides anti-rattle protection in high vibration applications

1-Pc Cable Tie/Fir Tree Mount with Disc, 7.1"L, 0.24 - 0.48" mounting hole, PA66, natural, 500/pkg

| | |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number | 157-00180 |
| Type | SG180FT62122A |
| Color | Natural (NA) |
| Quantity Per | bag |
| Product Description | Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie. |
| Short Description | 1-Pc Cable Tie/Fir Tree Mount with Disc, 7.1"L, 0.24 - 0.48" mounting hole, PA66, natural, 500/pkg |
| Global Part Name | SG180FT62122A-PA66-NA |

| | |
|-------------------------------------|-------------------------|
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 7.1 |
| Length L (Metric) | 180.0 |
| Fixation Method | Fir Tree for oval holes |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Outside Serrated |
| Width W (Imperial) | 0.20 |
| Width W (Metric) | 5.1 |
| Bundle Diameter Min (Imperial) | 0.04 |
| Bundle Diameter Min (Metric) | 1.0 |
| Bundle Diameter Max (Imperial) | 1.3 |
| Bundle Diameter Max (Metric) | 33.0 |
| Thickness T (Imperial) | 0.06 |

| | |
|-----------------------------------------|---------------|
| Thickness T (Metric) | 1.5 |
| Panel Thickness Min (Imperial) | 0.028 |
| Panel Thickness Max (Imperial) | 0.12 |
| Panel Thickness Min (Metric) | 0.7 |
| Panel Thickness Max (Metric) | 3.0 |
| Mounting Hole Diameter D (Imperial) | 0.24 x 0.48 |
| Mounting Hole Diameter D (Metric) | 6.2 x 12.2 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Imperial) | 0.48 |
| Mounting Hole Diameter D Max (Metric) | 12.2 |
| Disc Diameter (Metric) | 16.0 x 26.0 |
| Disc Diameter (Imperial) | 0.63 x 1.02 |

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL 94 V-2

| | |
|------------------------------|----------------------------------|
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)