

17

3309

signal max. 7 A\* 125 V (AC/DC)

2000 V

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

zinc diecast / chromated

PBT, UL 94 / V0 FKM

2000 m

500

3 III

-20 °C to 130 °C when connected IP 66/67

**Technical Data** 

rated insulation voltage (L-L)

number of pins

protection type

rotation range
Electrical Data

rated current rated voltage

mating cycles

Material

housing insulation insert

seals

pollution degree over voltage category

max. height for operation

Contacts (not part of product contents)

Tools (not part of product contents)

temperature range

## 623 Receptacle angled rotatable

speedtec

17-pin insulation insert Code 0° housing code 1 flange mount /Flange 28x28

## A ED C 139 NN 00 00 1100 000 A G C 139 N 00 00 1100 000



Contact Arrangement mating view




© 2018 TE Connectivity


TE Connectivity, TE connectivity (logo), intercontec (logo) and speedtec are trademarks.

While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information in this presentation, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this article are for reference purposes only and are subject to change without notice. Specifications and design specifications.

TE Connectivity Industrial GmbH Bernrieder Straße 15 94559 Niederwinkling, Deutschland Tel: +49 9962 2002-0 Fax: +49 9962 2002-70 E-Mail: intercontec@te.com Web: www.intercontec.biz







Main Dimensions Receptacle angled rotatable \*for max. wire cross-section pay attention to the cross-section of used contacts

Ø3.1 (4x)

ł

٠

D22,6 D28