

Slave protocol chip - IBS SUPI 3 OPC - 2746980

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Slave protocol chip, for INTERBUS

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	90 pc
Custom tariff number	85423990
Country of origin	United States

Technical data

Dimensions

Width	14 mm
Height	1.2 mm
Depth	14 mm
Length	14 mm

Ambient conditions

Ambient temperature (storage/transport)	5 °C ... 30 °C (at max. 60 %)
Ambient temperature (operation)	-40 °C ... 85 °C (at max. 75% humidity during operation)

Module

IC power supply voltage	5 V DC \pm 10 % (DC)
Typical current consumption	40 mA (without analog control)
Connection method	Remote bus/local bus or remote fiber optic bus
Interface	INTERBUS
Internal data length	4 bytes internally, external expansion is possible up to 64 bytes
User interface	MFP interface, digital I/O (2-8 IN/OUT, 16 IN/16OUT), SPI master interface (direct serial coupling to ADC/DACs) and serial microprocessor interface

General

Type	TQFP 64 (with copper block)
------	-----------------------------

Slave protocol chip - IBS SUPI 3 OPC - 2746980

Classifications

eCl@ss

eCl@ss 4.0	27250201
eCl@ss 4.1	27250201
eCl@ss 5.0	27250203
eCl@ss 5.1	27249201
eCl@ss 6.0	27242605
eCl@ss 7.0	27242605
eCl@ss 8.0	27242608

ETIM

ETIM 2.0	EC001433
ETIM 3.0	EC001601
ETIM 4.0	EC001601
ETIM 5.0	EC001604

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC
