

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		OPERATING TEMPERATURE RANGE		STORAGE TEMPERATURE RANGE	
		-35°C TO 85°C (NOTES 1)		-10°C TO 60°C	
RATING	OPERATING TEMPERATURE RANGE				
	VOLTAGE	30V AC		APPLICABLE CONNECTOR	
CURRENT	0.3A		DF37*-24DP-0.4V (**)		
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS		QT	AT
CONSTRUCTION			ACCORDING TO DRAWING.		
GENERAL EXAMINATION		CONFIRMED VISUALLY AND BY MEASURING INSTRUMENT.		X	X
MARKING		CONFIRMED VISUALLY.		X	X
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE		20mV AC OR LESS 1kHz, 1m A.		X	-
INSULATION RESISTANCE		100V DC.		X	-
VOLTAGE PROOF		100V AC FOR 1 min.		X	-
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION		10TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	
VIBRATION		FREQUENCY 10 TO 55 TO 10 Hz, APPROX 5min, SINGLE AMPLITUDE 0.75 mm, 100CYCLES, FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. OF PARTS. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	
SHOCK		490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. OF PARTS. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	
ENVIRONMENTAL CHARACTERISTICS					
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → 85°C TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER : WITHIN 2~3 MIN)		① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 50MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2°C, 90 TO 95%, 96 h.		① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 25MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	
SULPHUR DIOXIDE		EXPOSED IN 25 PPM FOR 96h, 25°C, 75%. (REFER TO JIS C 60068)		① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	
SALT MIST		EXPOSED IN 5% SALT MIST FOR 48h.		① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
△					
REMARKS					
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT					
Unless otherwise specified, refer to JIS C 5402 and IEC 60512					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-339438-01	
HRS SPECIFICATION SHEET		PART NO.	DF37NC(1.5)-24DS-0.4V(51)		
HIROSE ELECTRIC CO., LTD.		CODE NO.	CL684-3603-5-51		
				△	1/1