

Elastische Einpresszone / compliant pressfit zone

Isolierwerkstoff / housing material: PBT GF30

Bauart 7 / type 7

Anforderungsstufe 2 = 400 Steckzyklen / performance class 2 = 400 mating cycles

Fehlende Masse und Angaben nach IEC 60 603-2 / DIN EN 60 603-2


Missing information and dimensions per IEC 60 603-2 / DIN EN 60 603-2

Schichtaufbau im metallisierten Loch siehe Zeichnung 114124


diameter of drilled hole see drawing 114124

- 1) $\phi 1,0^{+0,09}_{-0,06}$ Durchmesser des metallisierten Loches
- $\phi 1,0^{+0,09}_{-0,06}$ Diameter of finished plated-through hole
- $\phi 1,15 \pm 0,025$ Bohrungsdurchmesser des Loches
- $\phi 1,15 \pm 0,025$ Diameter of drilled hole

Bestückungsplan / contact layout ■ bestückt / assembled



Leiterplatten-Lochbild / PCB drillhole pattern



Steckbare Codierung / Plugable Coding

Bei Änderung Variante 223527 (auf Transportpalette) beachten!

Information:		Tolerances	 All Dimensions in mm	Scale	2:1
All rights reserved. Only for information. To insure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation Federleiste C 96 EE Fem. Connector C 96 Pressfit	
 www.ERNI.com		204752		1	
c	14.08.2006	Date	H:00058708.SZA	STVC	

Consider protection memo from DN 34