



| JKL PART NUMBER | - A - LENGTH | COLOR 5000 °k                | STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C | OPERATING LAMP VOLTAGE VL (Vrms) | OPERATING LAMP CURRENT IL (mArms) | BRIGHTNESS (CANDELA/m2) | *RATED LIFE (HRS) |
|-----------------|--------------|------------------------------|--|----------------------------------|-----------------------------------|-------------------------|-------------------|
| CF26346-37B     | 346±3.0      | x = .345±.01<br>y = .360±.01 | 1450                                     | 700                              | 6± 1                              | 36,000±15%              | 40,000            |
| CF26397-37B     | 397±3.0      |                              | 1520                                     | 725                              |                                   |                         |                   |
| CF26448-37B     | 448±3.0      |                              | 1820                                     | 870                              |                                   |                         |                   |
| CF26499-37B     | 499±3.0      |                              | 2100                                     | 1000                             |                                   |                         |                   |
| CF26550-37B     | 550±3.0      |                              | 2270                                     | 1100                             |                                   |                         |                   |
| CF26600-37B     | 600±3.0      |                              | 2340                                     | 1125                             |                                   |                         |                   |

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

|  |  |  |  |   |                          |                                 |                           |                   |                 |
|--|--|--|--|---|--------------------------|---------------------------------|---------------------------|-------------------|-----------------|
|  |  | <b>METRIC</b><br>DIMENSIONS ARE IN MILLIMETERS<br>TOLERANCE UNLESS OTHERWISE SPECIFIED<br>1 PL +/- 0.2<br>2 PL +/- 0.20<br>ANGLE +/- 0 |  | <h1>JKL COMPONENTS CORPORATION</h1>                     |                          |                                 |                           |                   |                 |
|  |  | THIRD ANGLE PROJECTION   |  | <b>TITLE</b><br>MINIATURE COLD CATHODE FLUORESCENT LAMP |                          |                                 |                           |                   |                 |
| DRAWN BY<br>L. WENGSTROM                               |  | APPV'D BY DATE<br>J.K. 11/18/04  |  | SIZE<br><b>A</b>  | FSCM NO.<br><b>55335</b> | DRAWING NO.<br><b>CF 26-37B</b> |                           |                   |                 |
| CHANGE LENGTH & PART NO.<br>RELEASE & CANCEL P-0410-05 |  | 11/18/04<br>11/17/04   |  | <b>- CAD DRAWING -</b>                                  |                          |                                 |                           |                   |                 |
| REV. NO. DESCRIPTION/ECO NUMBER                        |  | APPV'D DATE  |  | SCALE<br><b>NONE</b>                                    |                          | RELEASED DATE<br>11/17/04       | REVISION DATE<br>11/18/04 | REV. NO. <b>A</b> | SHEET<br>1 OF 1 |