



- 注
1. APPLICABLE WIRE IS AWG #20(C. 5sq)~#22(C. 3sq) OF STRANDED CABLE.
 2. APPLICABLE CRIMPING MACHINE AND CRIMPING CONDITIONS (CRIMP HEIGHT etc.) WILL BE SPECIFIED ACCORDING TO AWG # OR WIRE APPLIED.
 3. ONE PACKAGE CONSISTS OF 100 PCS.
 4. THIS PRODUCT IS ASSEMBLED WITH TJS0A-41S-※.
 5. REFER TO ATAI-E3050 FOR CRIMP QUALITY STANDARDS.

NO.	1	REVISIONS	NO.	1	DATE	15.04.28
MATERIAL	COPPER ALLOY	FINISH	TERMINAL AREA : TIN PLATING UNDER PLATING : NICKEL PLATING	REMARKS	CONTACT AREA : GOLD PLATING 0.76μm	

NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS
1	COPPER ALLOY	TERMINAL AREA : TIN PLATING UNDER PLATING : NICKEL PLATING	CONTACT AREA : GOLD PLATING 0.76μm				

UNITS	mm	SCALE	5 : 1
APPROVED	MM. NISHIMATSU	CHECKED	MM. NISHIMATSU
DESIGNED	MO. SHIMOYAMA	DRAWN	MO. SHIMOYAMA
DATE	15.04.28	DATE	15.04.28
DRAWING NO.	EDC-128057-00-00	PART NO.	TJS0A-2022SCA
CODE	CL236-3104-9-00		

HRS

HIROSE
ELECTRIC
CO., LTD.