GlobTek, Inc.	Drawing Title: Power Din Plug, 4P, Snap and Lock, White, supplied in kit, ready to assemble				
www.globtek.com	Model No. High Power DC Connectors				
186 Veterans Drive,					
Northvale, NJ 07647					
Tel. (201) 784-1000	Part No./Ordering No. GTPWRDIN4LW	Rev A2			
Fax (201) 784-0111					

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at http://www.globtek.com/iso-certificates/

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (http://en.globtek.com/terms-and-conditions/).

Prop 65 Statement:https://en.globtek.com/prop-65-statement.pdf

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.

Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing. A delay in receipt of this form will delay delivery schedule.

Company Name:	Customer P/N:
Quote Number:	Date:
Authorized Representative Name:	Authorized Representative Signature:

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2020 - 2023 guest /08/15/2023 5:19:03 AM CLONED FROM L01

GlobTek, Inc.	Drawing Title: Power Din Plug, 4P, Snap and Lock, White, supplied in kit, ready to assemble	
www.globtek.com	Model No. High Power DC Connectors	
186 Veterans Drive,		
Northvale, NJ 07647		
Tel. (201) 784-1000	Part No./Ordering No. <u>GTPWRDIN4LW</u>	Rev A2
Fax (201) 784-0111		

REV	DESCRIPTION				SUB	DATE	APPROVED
A2	Add a link to the assembly instructions P/	N : PWRDINCO	NNECTOR_ASSEMBLY	/ INSTRUCTIONS	QA	07/18/2022	QA
A1 Update the locking latch detail			QA	06/21/2020	QA		
A	Initial release				DR	05/28/2020	QA
AGEN	ICY ONLINE DOCUMENTS						
RoHS	/RoHS3 Declaration	https:/	//www.globtek.com/p	odf/rohs_cert/01t3a00	0004GWEYAA4		
REAC	CH Declaration			odf/iso_certificates/RI			
Confli	ict Minerals Declaration			df/conflict-minerals.p			
Prop	65 Statement		/en.globtek.com/pro				
PXY	rating is based on 3rd party testing a				level IPXY rating befo	re ordering.	
Drawi	ng:		10.010.0				
	h -(49 .2± 0.3				
	-	36	.2				
		30,9					
	-		-				
		5.5±0.3					
			Ч	⊸⁻─┧ ╊┲┲┲┲┲			
					HI		
₩	╫╪ <mark>╫╷╶┨</mark> ╞══──				-		
7					HI		
			Ļ				
			000			0.0	0
		-		>			
						00	
	ng Assembly detail: Standard and on	this item:	K -1	Opti	onal cover upon reque	st	
under	different part #)						
Electr	ical Specification:						

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2020 - 2023 guest /08/15/2023 5:19:03 AM CLONED FROM L01

GlobTek, Inc. www.globtek.com	Drawing Title: Power Din Plug, Model No. High Power Din Plug,	4P, Snap and Lock, White, supplied in kit, ready to assemble	
186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Part No./Ordering No. G	TPWRDIN4LW	Rev A2
Current /Vol	tage	Pin 1, 2, 3, 4 : 7.5Amax/54VDC contacts designed for AWG18 max wire	

Insulation resistance	≥50MΩ	250VDC					
Contact resistance	≤30 mΩ						
Withstand voltage (pin to pin)	250VAC	C / 1min					
Lifetime	≥5000						
Operation Temperature	-20°C- 5	50°C					
Mechanical Specification: Body: ABS, UL 94HB Rated Insert: Nylon, UL 94V-2 Rated Inner Shield: Copper Alloy, Nickel Plated Contacts: Brass, Silver Plated Insertion Force: 4.5KG Max Pull Force: 1.0-4.5KG unlocked, 4.5KG Min locked. Durability: 5000 cycles Color: GlobTek White, Similar to RAL9003 "Signal White	ite"						
Pin contacts designed for AWG18 max wire.							
Each set is individually bagged.							
Mates with: KPJX-CM-4S KPJX-PM-4S KPJXHT-4	S KPJX-4S	KPJX-PM-4S-S	KPJXHT-4S-S	PD-40VS	PD-40V	PD-40	PD-40S

Assembly instructions P/N : PWRDINCONNECTOR_ASSEMBLY INSTRUCTIONS:

https://globtek.secure.force.com/spec/pdf/2320697/d2738500

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2020 - 2023 guest /08/15/2023 5:19:03 AM CLONED FROM L01

GlobTek, Inc.	Drawing Title: Power Din Plug, 4P, Snap and Lock, White, supplied in kit, ready to assemble	
www.globtek.com	Model No. High Power DC Connectors	
186 Veterans Drive,		
Northvale, NJ 07647		
Tel. (201) 784-1000	Part No./Ordering No. GTPWRDIN4LW	Rev A2
Fax (201) 784-0111		

PACKAGING

Packing Spec P/N:	
Box Qty:	1000
Gift Box Size (mm):	
Gift Box Color:	White
Master Carton Size (mm):	TBD
Master Carton Cubic Volume (m ³):	0.00
Master GW (Kg):	kg
wt Ea. (Kg):	kg
wt Ea. (Kg):	kg
LABEL SPECS: ,	
PACK SPEC:	

PROPRIETARY INFORMATION PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2020 - 2023 guest /08/15/2023 5:19:03 AM CLONED FROM L01