

WSA350

BENCHTOP SMOKE ABSORBER

THE WELLER ADVANTAGE:

The WSA350 removes flux fumes from the benchtop by drawing the smoke through an activated carbon filter. Powered by an exceptionally quiet fan, the WSA350 can process up to 1.37 cubic meters of air per minute. The collector can be easily adjusted to multiple positions, optimizing its fume-absorbent performance.



- Removes flux fumes from soldering workbench
- Great for workspaces using more active fluxes used with lead-free solder
- Fumes are absorbed by the replaceable carbon-activated filter
- Includes one replaceable filter
- Stand allows the smoke absorber to be adjusted to varying angles
- Fan is quiet and will not add significant noise to the workspace
- ESD safe
- Package of 3 replacement filters. Part No. WSA350F

WSA350 Specifications:

Voltage 120 Vac
Air Consumption 87-107 CFM
Sound Level 45-50 dB (A)
Power Consumption 20W

Power Consumption 20W 1.25 m³/min. (50 Hz) to 1.37 m³/min. (60 Hz)

ESD Safe Yes UL and cUL Listed Yes

Distributed by: All-Spec, a Hisco Subsidiary

Wilmington, NC

WSA350F Specifications:

Filters per pack Size

ze 130mm x 130mm x 10mm

Activated carbon content per filter Maximum capacity for noxious components

9g

per filter 2.5g

Ph: 800-537-0351 Web: <u>www.all-spec.com</u>
Fx: 800-379-9903 Email: <u>sales@all-spec.com</u>

