

FireNEX™ -5000H+

2-Port USB 3.0/2.0/1.1 Optical Fiber Repeater



Data Sheet



Description

FireNEX-5000H+™ is the latest USB SuperSpeed optical fiber extension solution from Newnex. In addition to the capability of extending USB SuperSpeed 5Gbps data up to 300 meters via a optic fiber cable, It can also support USB 2.0/1.1 lower speed peripherals which are still widely used.

FireNEX™-5000H+ contains one Local Unit for connection to the host computer and one Remote Unit with two stacked USB Type-A Downstream Ports for device connections. The USB ports on both Local Unit and Remote Unit are all featured with USB3 Vision standard compliant locking ports to ensure interconnections with cables are secure.

Included in the Box

- 1x FIRENEX-5000H+ Local Unit
- 1x FIRENEX-5000H+ Remote Unit
- 1x 12V DC Power Adapter (US)
- 1x USB A to B Host Cable, 1m
- 1x FIRENEX-5000H+ User Manual

Features

- 100% Plug and Play
- Support 5Gbps SuperSpeed USB 3.1 Gen 1
- USB 2.0/1.1 Backward Compatible with Windows OS
- Extension Distance up to 300 meters
- Compact Size and Light Weight
- Durable Metal Enclosure
- AIA USB3 Vision® Compliant Locking Ports
- RoHS Compliant

Ordering Information

Please contact Newnex sales team or your local distributors for ordering information, at www.newnex.com/wheretobuy.php. For technical information and support, please visit Newnex Technology Corp's web at www.newnex.com or contact 1-408-986-9988

Specification

RANGE

Max. Extension Up to 300m (1,000 ft.)

DATA RATE

USB 3.0 SuperSpeed 5 Gb/s
USB 2.0/1.1 Backward Compatible on Windows OS

LOCAL Unit

Dimensions 106 x 45.4 x 27mm (4.17 x 1.79 x 1.06")
Weight 135 g
Enclosure Material Anodized Aluminum
USB Connector 1x USB 3.0 Type-B Locking Port
Compliant with AIA USB3 Vision Standard
Optical Connector 1x Duplex LC Connector
Power Source 5V USB Bus Powered

REMOTE Unit

Dimensions 106 x 45.4 x 27mm (4.17 x 1.79 x 1.06")
Weight 139 g
Enclosure Material Anodized Aluminum
USB Connector 2x USB 3.0 Type-A Locking Port
Compliant with AIA USB3 Vision Standard
Optical Connector 1x Duplex LC Connector
Power Input 12-24V DC
Power In Connector 2.1mm Center Positive
USB Power Output 2500mA for each USB Port

COMPATIBLE FIBER CABLE

Length Up to 300m (1,000 ft.)
Type OM3 or OM4, 50/125µm, Multi-mode, Duplex LC

POWER SUPPLY

AC Power Plug Type US/EU/UK/CN
Power Input 100-240V AC, 50/60Hz, 0.8A
Power Output 12V DC, 2.5A

ENVIRONMENTAL

Operating Temperature -10°C to 85 °C (14°F to 185°F)
Storage Temperature -65°C to 150 °C (-85°F to 302°F)
Operating Humidity 20% to 80% relative humidity, non-condensing
Storage Humidity 10% to 90% relative humidity, non-condensing

COMPLIANCE AND COMPATIBILITY

Connectivity USB 3.0
Machine Vision Mechanical AIA USB3 Vision[®] Compliant
EMC FCC, CE
Environmental RoHS
Laser Safety IEC 60825-1 Class 1/CDRH Class 1 laser eye safe

SUPPORT

Warranty 1-year Manufacture Warranty
