


REV.	ECN NO.	REVISIONS	DRN.	CKD.	APP.	DATE
A	—	NEW RELEASE	JAV			



NOTES:

1. LENS COLOR: WATER CLEAR (NON-TINTED, NON DIFFUSED).
2. DIE: In GaN BLUE COATED WITH PHOSPHOR TO PRODUCE WHITE.
3. LEAD SPACING MEASURED NEAR EPOXY PACKAGE.
4. DIALIGHT PART NUMBER: 521-9901

OPERATING CHARACTERISTICS AT 25°C AMBIENT

LED CHARACTERISTICS	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
LUMINOUS INTENSITY	520		1500	mc d	I _F = 20mA
FORWARD VOLTAGE		3.6	4.0	V	I _F = 20mA
REVERSE CURRENT	10			μA	V _R = 5V
VIEWING ANGLE (2θ _{1/2})		45		DEG.	

ABSOLUTE MAXIMUM RATINGS AT 25°C AMBIENT	VALUE	UNITS
POWER DISSIPATION	120	mW
LINEAR DERATION FROM 55°C	0.7	mA/°C
FORWARD DC CURRENT	30	mA
PEAK FORWARD CURRENT (≤ 1/10 DUTY CYCLE TW ≤ 10 msec.)	100	mA
REVERSE VOLTAGE @ I _R = 10μA	5	V
OPERATING TEMPERATURE	-40 TO +80	°C
STORAGE TEMPERATURE	-40 TO +100	°C
DIP-DRAG SOLDER TEMPERATURE	260 FOR 5 SEC.	°C
WAVE SOLDER TEMPERATURE	245 FOR 3 SEC.	°C

BIN	LIMITS (CHROMATICITY COORDINATES)				
	X	Y	Z	U	
1	X	0.330	0.330	0.356	0.361
	Y	0.360	0.318	0.351	0.385
2	X	0.287	0.296	0.330	0.330
	Y	0.295	0.276	0.318	0.339
3	X	0.264	0.280	0.296	0.283
	Y	0.267	0.248	0.276	0.305
4	X	0.283	0.287	0.330	0.330
	Y	0.305	0.295	0.339	0.360

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT.

SCALE 6:1		DRAWING NUMBER	REV
ALL DIM'S IN: INCHES (MM)		C-17090	A
TOLERANCES: UNLESS OTHERWISE SPECIFIED		TITLE ∅ 3.0 mm WHITE LED	
FRACTIONS: ±1/64 DECIMALS (.XX): ±.01 DECIMALS (.XXX): ±.008		MATERIAL	
ANGLES: ±1°		Dialight	
FINISH:		1501 ROUTE 34 SOUTH FARMINGDALE, NJ 07727	
FSCM 83330		SHEET OF FAMILY TABLE:	