



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00540	Connector, dc plug, 5.5x2.1x23 mm, molding style, spring contacts, nickel plated, 105° C	1	
2	30-01248	Wire, 2C, 18 AWG, UL4384, 300V, 105 °C, 4.4 mm, VW-1, LSZH, XLPE	1	
3	24-00190	Overmold, 90°, dc plug	1	TPE, 105 °C, black



Wiring Diagram	
50-00540	wire color
center	black with stripe
sleeve	black

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	10/03/2018	Initial release	RS <small>Digitally signed by RS Date: 2018.10.04 09:26:32 -07'00'</small>	RoHS compliant	
			Verified: JP <small>Digitally signed by JP Date: 2018.10.04 09:31:32 -07'00'</small>	Function test: no open, no short circuit, no intermittent	
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Low smoke, zero halogen	
				Description: Cable, 1830 mm, 5.5x2.1x10 mm 90° 50-00540 dc plug to 10 mm tinned, 18 AWG, 30-01248, LSZH	
				Size:	Part number:
				A	10-03132
				Scale: 1:1	Sheet 1 of 1

5

4

3

2

1