

CUC-PPC-A2RBK-PC - Protective cover



1424989

<https://www.phoenixcontact.com/us/products/1424989>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Protective cover, degree of protection: IP65, number of positions: 2



Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1424989 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | AB12 |
| Product key | ABNOJZ |
| Catalog page | Page 364 (C-2-2019) |
| GTIN | 4055626386591 |
| Weight per piece (including packing) | 10.7 g |
| Weight per piece (excluding packing) | 10.7 g |
| Customs tariff number | 85389099 |
| Country of origin | DE |

CUC-PPC-A2RBK-PC - Protective cover



1424989

<https://www.phoenixcontact.com/us/products/1424989>

Technical data

Product properties

| | |
|---------------------|-----------|
| Product type | Data plug |
| Number of positions | 2 |

Insulation characteristics

| | |
|----------------------|---|
| Overvoltage category | I |
| Degree of pollution | 2 |

Dimensions

| | |
|--------|---------|
| Width | 22 mm |
| Height | 55.7 mm |
| Depth | 21 mm |
| Length | 34 mm |

Material specifications

| | |
|--|------------|
| Material | Plastic |
| Flammability rating according to UL 94 | V0 |
| Seal material | NBR NBR |
| Locking latch material | PA |

Cable/line

| | |
|-----------------------------|-----------------|
| External cable diameter () | 4.5 mm ... 8 mm |
|-----------------------------|-----------------|

Environmental and real-life conditions

Ambient conditions

| | |
|---|------------------|
| Degree of protection | IP65 |
| Ambient temperature (operation) | -40 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Ambient temperature (assembly) | -5 °C ... 55 °C |

CUC-PPC-A2RBK-PC - Protective cover



1424989

<https://www.phoenixcontact.com/us/products/1424989>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1424989>



EAC

Approval ID: B.01687

CUC-PPC-A2RBK-PC - Protective cover



1424989

<https://www.phoenixcontact.com/us/products/1424989>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC002635 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

CUC-PPC-A2RBK-PC - Protective cover



1424989

<https://www.phoenixcontact.com/us/products/1424989>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

CUC-PPC-A2RBK-PC - Protective cover

1424989

<https://www.phoenixcontact.com/us/products/1424989>



Accessories

VS-PPC-C2-MSTB-MNNA-P13-A5-SP - Power connector

1608074

<https://www.phoenixcontact.com/us/products/1608074>



Power connector, degree of protection: IP65, number of positions: 5, material: Zinc die-cast, connection method: Spring-cage connection, connection cross section: AWG 18- 13, cable outlet: straight, color: silver

CUC-V14-F2ZNI-EM/24FN5:FC - Panel feed-through

1408235

<https://www.phoenixcontact.com/us/products/1408235>



Push/pull panel mounting frame, metal, version 14, including contact insert with spring-cage connection, flexible coding, for rectangular mounting cutout, with seal, without fixing screws

CUC-PPC-A2RBK-PC - Protective cover

1424989

<https://www.phoenixcontact.com/us/products/1424989>



VS-PPC-F2-MSTB-MNNA-1R-P - Panel mounting frames

1608087

<https://www.phoenixcontact.com/us/products/1608087>



MSTB panel mounting frame, IP67, for push-pull interlocking, metal, for PCB connection, for square panel cutout, with grommet, without mounting screws

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com