

Click Connectors

for LED linear lighting | not to be used in wet locations

SIZE	ACTUAL WIDTH	PRODUCT COMPATIBILITY	DRIVER COMPATIBILITY	FLYING WIRE LEAD LENGTH
8MM	11.9mm / 0.46"	T150, T300, TSHL5050-150, TSHL2825 series, and TUB5630 series, T150RGB, T300RGB, T300RGBWW, T300RGBCW	only class 2 power unit	3", 6", 12", 24", 36", 60" or specify custom length (not available for TSPLICE connector)
10MM	14.1mm / 0.55"			
14MM	19.55mm / 0.77"			



TCON-CL TCONNECT
single slide linear lighting connector to flying wire lead



TPWR-CL TPOWERCONNECT
linear lighting to power supply slide connector



TYCON-CL TYCONNECT
single slide linear lighting connector to 2 additional linear lighting runs



TYPWR-CL TYPOWERCONNECT
single power connector to 2-way split slide linear lighting connectors



TCOR-CL TCORNER
single slide linear lighting connector to additional linear lighting run



TSPL-CL TSPLICE
single connector for 2 runs of linear lighting (the top of the connector has a red dot)

code	lighting type	connector type	size	length (inches)	ORDER
T	[BLANK]	YCON-CL	8MM	12	
sample order:	[BLANK] RGB RGBW <small>leave blank for non-color-changing lighting</small>	CON-CL YCON-CL COR-CL PWR-CL YPWR-CL SPL-CL	8MM 10MM 14MM	3 6 12 24 36 60 Custom	

		8mm	10mm	connected runs	90° TURNS
TLCORNER		TLCOR-CL TLRGBCOR-CL	1.15" x 1.15" 29.21mm x 29.21mm	1.25" x 1.25" 31.75mm x 31.75mm	2
TTCORNER		TTCOR-CL TTRGBCOR-CL	1.75" x 1.15" 44.50mm x 29.21mm	2" x 1.25" 50.80mm x 31.75mm	3
TXCORNER		TXCOR-CL TXRGBCOR-CL	1.75" x 1.75" 44.50mm x 44.50mm	2" x 2" 50.8mm x 50.8mm	4