24 INCHES LENGTH





Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 122148 TNC Plug Right Angle Brass Nickel + Heatshrink

Connector B

Assembly & Label Notes

Connector A

Assembly label to be placed \sim 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.



		1		4	
132245	Part #:	RG-174	Part #:	122148	
SMA R/A BHD JK RG174 RG316 LMR100	Description:	RG-174 - PE 0.1	Description:	TNC R/A PLUG RG174 RG188 RG316 500	
500	Dielectric:	PE	Type:	TNC	
SMA	Shielding:	Braid	Gender:	Plug	
Jack	Diameter:	0.1	Body Type:	Right Angle	
Right Angle	Impedance:	50 Ohm	Contact Type:	Solder	
Solder	Sheathing:	None	Polarity:	Standard	
Standard	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm	
50 Ohm	_	24 Inches	I '	Cable	
Bulkhead - Rear Mount	1		_ ~	Brass	
Brass			1 '	Nickel	
Gold			1 '	None	
None				Brass	
Beryllium Copper				Gold	
Gold				11 GHz	
12.4 GHz			· ·	TNC Plug Right Angle	
SMA Jack Right Angle			Clocking:	0°	
	SMA R/A BHD JK RG174 RG316 LMR100 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz	SMA R/A BHD JK RG174 RG316 LMR100 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz	SMA R/A BHD JK RG174 RG316 LMR100 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz Description: RG-174 - PE 0.1 Dielectric: PE Shielding: Braid Diameter: 0.1 Impedance: 50 Ohm Sheathing: None Testing: Continuity Hi-Pot Length: 24 Inches	SMA R/A BHD JK RG174 RG316 LMR100 500 SMA Jack Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz Description: RG-174 - PE 0.1 Dielectric: PE Shielding: Braid Diameter: 0.1 Impedance: 50 Ohm Sheathing: None Testing: Continuity Hi-Pot Length: L	

Cable



THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-RA-JK/TNC-RA-PL G174 24I

Part No

Q-2P04T0003024I

UNLESS SPECIFIED TOLERANCE:

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES