



TECHNICAL

AGENCY APPROVAL:	cULus
RATED SUPPLY VOLTAGE:	120VAC
RATED CURRENT:	15A
RESET TYPE:	MANUAL
OPERATING FREQUENCY:	60 Hz
TYPE:	CLASS A
GROUND TRIP CURRENT:	4-6 mA
OVERLOAD CURRENT:	90 AMP
INSULATION VOLTAGE:	1,500 VRMS - 1 MINUTE
ENDURANCE OPERATIONS:	3000 OPERATIONS
ENCLOSURE:	NEMA 3R

MATERIAL NUMBER	ENGINEERING NUMBER	LENGTH "A"	LENGTH "L"
1301530054	15052-1	9.50 IN.	1 FT. 11.4 IN.
1301530067	15052-6	4 FT. 10.50 IN.	6 FT. 0.4 IN.
1301530060	15052-25	23 FT. 10.50 IN.	25 FT. 0.4 IN.
1301530064	15052-50	48 FT. 10.50 IN.	50 FT. 0.4 IN.
1301530055	15052-100	98 FT. 10.50 IN.	100 FT. 0.4 IN.

FUNCTIONAL SYMBOLS E=0 E=0 E=0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		molex				
	DIMENSION UNITS	SCALE			GFCI IN-LINE 15A W/WATERTITE PLUG & CONNECTOR		
	INCH	NTS	PRODUCT CUSTOMER DRAWING				
	GENERAL TOLERANCES (UNLESS SPECIFIED)		DOCUMENT NUMBER				
ANGULAR TOL ± °		1301530067					
4 PLACES ±		PSD 000 B					
3 PLACES ±		MATERIAL NUMBER					
2 PLACES ±		CUSTOMER					
1 PLACE ±		SEE TABLE					
0 PLACES ±		GENERAL MARKET					
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
			B-SIZE	130153	SEE TABLE	GENERAL MARKET	1 OF 1