

0.25 METER LENGTH



Connector A  
031-70544-12G  
BNC Plug Right Angle  
Brass Nickel + Heatshrink

75 Ohm 4855R  
Continuity/Hi-Pot

Connector B  
031-70538-12G  
BNC Jack Straight  
Brass Nickel + Heatshrink

**Assembly & Label Notes**

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink  
Assembly shall be built with SN96.5 LEAD FREE solder.  
See Routing Notes for additional assembly & testing instructions.

Connector A		Cable		Connector B	
<b>Part #:</b>	031-70544-12G	<b>Part #:</b>	4855R	<b>Part #:</b>	031-70538-12G
<b>Description:</b>	BNC R/A PLUG Belden 4855R RG59 MINI 75O	<b>Description:</b>	4855R - FHDPE 0.159	<b>Description:</b>	BNC Jack Belden 4855R RG59 MINI 75O
<b>Type:</b>	BNC	<b>Dielectric:</b>	FHDPE	<b>Type:</b>	BNC
<b>Gender:</b>	Plug	<b>Shielding:</b>	Braid	<b>Gender:</b>	Jack
<b>Body Type:</b>	Right Angle	<b>Diameter:</b>	0.159	<b>Body Type:</b>	Straight
<b>Contact Type:</b>	Crimp	<b>Impedance:</b>	75 Ohm	<b>Contact Type:</b>	Crimp
<b>Polarity:</b>	Standard	<b>Sheathing:</b>	None	<b>Polarity:</b>	Standard
<b>Impedance:</b>	75 Ohm	<b>Testing:</b>	Continuity Hi-Pot	<b>Impedance:</b>	75 Ohm
<b>Mounting:</b>	Cable	<b>Length:</b>	0.25 Meter	<b>Mounting:</b>	Cable
<b>Body Material:</b>	Brass			<b>Body Material:</b>	Brass
<b>Body Finish:</b>	Nickel			<b>Body Finish:</b>	Nickel
<b>IP Rating:</b>	None			<b>IP Rating:</b>	None
<b>Contact Material:</b>	Brass			<b>Contact Material:</b>	Phosphor Bronze
<b>Contact Finish:</b>	Gold			<b>Contact Finish:</b>	Gold
<b>Max. Freq.:</b>	18 GHz			<b>Max. Freq.:</b>	12 GHz
<b>Booting:</b>	BNC Plug Right Angle			<b>Booting:</b>	BNC Jack Straight
				<b>Clacking:</b>	0°



**CONTROLLED DOCUMENT - DO NOT COPY**

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:  
**BNC-RA-PL/BNC-ST-JK BLD485R 0.25M**

Part No:  
**Q-62063000K.25M**

**UNLESS SPECIFIED**  
TOLERANCE:  
0-18 inches +/- 1/2"  
over 18" +/- 2%  
ASSEMBLY:  
CENTER LABEL IF LENGTH  
IS LESS THAN 12 INCHES