

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
APPLICATION STANDARD										
	OPERATING TEMPERATURE RANGE	-55 °C TO +85 °C				STORAGE TEMPERATURE RANGE	— °C TO — °C			
	RATING VOLTAGE	100 V AC				OPERATING HUMIDITY RANGE	— % TO — %			
	CURRENT	0.4 A				APPLICABLE CABLE	—			
SPECIFICATIONS										
ITEM					TEST METHOD					
CONSTRUCTION					REQUIREMENT					
GENERAL EXAMINATION					VISUALLY AND BY MEASURING INSTRUMENT ACCORDING TO DRAWING					
MARKING					CONFIRMED VISUALLY					
ELECTRICAL CHARACTERISTICS										
CONTACT RESISTANCE					100 mA (DC OR 1000 Hz) 45 mΩ MAX.					
MILLIVOLT LEVEL METHOD					20 mV MAX, 1 mA (DC OR 1000 Hz) 55 mΩ MAX.					
INSULATION RESISTANCE					250 V DC 100 MΩ MIN.					
VOLTAGE PROOF					300 V AC FOR 1 min. NO FLASHOVER OR BREAKDOWN					
MECHANICAL CHARACTERISTICS										
CONTACT INSERTION AND EXTRACTION FORCES					BY STEEL GAUGE.					
INSERTION AND WITHDRAWAL FORCES					MEASURED BY APPLICABLE CONNECTOR.					
MECHANICAL OPERATION					50 TIMES INSERTION AND EXTRACTIONS.					
VIBRATION					FREQUENCY: 10 TO 55 Hz, SINGLE AMPLITUDE: 0.75 mm, · m/s ² AT 2 h FOR 3 DIRECTIONS.					
SHOCK					490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.					
ENVIRONMENTAL CHARACTERISTICS										
DAMP HEAT (STEADY STATE)					EXPOSED AT 40±2 °C, 90~95 %, 96 h.					
RAPID CHANGE OF TEMPERATURE					TEMPERATURE -55~+5~+35~+85~+5~+35°C TIME 30~10~15~30~10~15 min. UNDER 5 CYCLES.					
DAMP HEAT, CYCLIC					EXPOSED AT % TOTAL TO °C, TO °C, TO °C, h. TO h.					
DRY HEAT					EXPOSED AT °C, h.					
CORROSION SALT MIST					EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.					
HYDROGEN SULPHIDE					EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA-38)					
SULPHUR DIOXIDE					EXPOSED IN PPM FOR h. (TEST STANDARD: JEIDA-39)					
RESISTANCE TO SOLDERING HEAT					SOLDER TEMPERATURE, °C FOR s. °C FOR s.					
SOLDERABILITY					SOLDERED AT SOLDER TEMPERATURE, °C FOR IMMERSION DURATION, s.					
REMARKS										
UNLESS OTHERWISE SPECIFIED, REFER TO JIS C 5402.			DRAWN		DESIGNED		CHECKED		APPROVED	
NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST O: APPLICABLE TEST			S. Naito		Matsubara		M. Tani		Miyahara	
CODE NO.(OLD)			DRAWING NO.		CODE NO.		PART NO.		RELEASED	
CL			SLC4-150730-01		CL 578		FX8-***S-SV(21)		1	
FORM NO. 231-1										

TO
PCM

