

SPECIFICATIONS:

MATERIAL:-
 MOULDING: NYLON 9T, UL94V-0
 CONTACT: PHOSPHOR BRONZE, 0.3MM FLAT PIN
 FINISH:-
 TIN PLATED
 ELECTRICAL:-
 CURRENT RATING: 1A AC/DC MAX.
 WORKING VOLTAGE: 100V AC/DC
 WITHSTAND VOLTAGE: 500V AC/MINUTE
 CONTACT RESISTANCE: 20 mΩ MAX.
 INSULATION RESISTANCE: 100 MΩ MIN.
 ENVIRONMENTAL:-
 TEMPERATURE RANGE: -25°C TO +85°C
 OTHERS:-
 MATE WITH HOUSING M30-130 XX 46

NOTES: ALL DIMENSIONS AND NOTES MARKED * ARE CRITICAL AND MUST BE CHECKED IN ACCORDANCE WITH QUALITY DOC. QI-02A

PART NO	PIN	DIM (MM)			
		A	B	C	D
M30-4010246R	02	--	3.40	3.70	7.25
M30-4010346R	03	2.50	4.35	4.95	8.50
M30-4010446R	04	3.75	5.60	6.20	9.75
M30-4010546R	05	5.00	6.85	7.45	11.00
M30-4010646R	06	6.25	8.10	8.70	12.25
M30-4010746R	07	7.50	9.35	9.95	13.50
M30-4010846R	08	8.75	10.60	11.20	14.75
M30-4010946R	09	10.00	11.85	12.45	16.00
M30-4011046R	10	11.25	13.10	13.70	17.25
M30-4011146R	11	12.50	14.35	14.95	18.50
M30-4011246R	12	13.75	15.60	16.20	19.75
M30-4011346R	13	15.00	16.85	17.45	21.00
M30-4011446R	14	16.25	18.10	18.70	22.25
M30-4011546R	15	17.50	19.35	19.95	23.50
M30-4011646R	16	18.75	20.60	21.20	24.75
M30-4011746R	17	20.00	21.85	22.45	26.00
M30-4011846R	18	21.25	23.10	23.70	27.25
M30-4011946R	19	22.50	24.35	24.95	28.50
M30-4012046R	20	23.75	25.60	26.20	29.75

OBSOLETE

Mating Condition (REF.)

*NOTE: REMOVE R FOR LOOSE BAG PACKING

ORDER CODE

M30-401 XX 46R

NO. OF WAYS WITH R: REEL PACKING
 WITHOUT R: LOOSE BAG PACKING
 (10pcs Per Strip, 10 Strips per Bag)

Leo	5	27.06.14	A431
Allan	4	06.10.08	A166
Allan	3	04.07.09	A141
Allan	2	02.07.08	A139
Allan	1	18.09.06	-

NAME	ISS.	DATE	C/NOTE
APPROVED:		B.Lim	
CHECKED:		D.P	
DRAWN:		Leo	
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

HARWIN USA
 TEL: 603 893 5376
 FAX: 603 893 5396
 mis@harwin.com

HARWIN Europe (UK)
 TEL: 023 9231 4545
 FAX: 023 9231 4590
 mis@harwin.co.uk







HARWIN Asia
 TEL: +65 6 779 4909
 FAX: +65 6 779 3868
 mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
 X.X = ±0.25mm
 X.XX = ±0.15mm
 ANGLES = ±5°
 UNLESS STATED

MATERIAL: SEE NOTES
 FINISH: SEE NOTES
 S/AREA: mm?

TITLE: HEADER P=1.25MM SMT R/A TYPE
 DRAWING NUMBER: M30-401 XX 46R
 SHT 1 OF 2



PIN	DIM (MM)				
	B0	F	W	W1	S
02	7.65	7.50	16.00	16.50	--
03	8.90	7.50	16.00	16.50	---
04	10.15	7.50	24.00	24.50	---
05	11.40	11.50	24.00	24.50	---
06	12.65	11.50	24.00	24.50	---
07	13.90	11.50	24.00	24.50	---
08	15.15	11.50	24.00	24.50	---
09	16.40	11.50	24.00	24.50	---
10	17.65	11.50	32.00	32.50	---
11	18.90	14.20	32.00	32.50	28.40
12	20.15	14.20	32.00	32.50	28.40
13	21.40	14.20	32.00	32.50	28.40
14	22.65	20.20	44.00	44.50	40.40
15	23.90	20.20	44.00	44.50	40.40
16	25.15	20.20	44.00	44.50	40.40
17	26.40	20.20	44.00	44.50	40.40
18	27.65	20.20	44.00	44.50	40.40
19	28.90	20.20	44.00	44.50	40.40
20	30.15	20.20	44.00	44.50	40.40

NOTES: ALL DIMENSIONS AND NOTES MARKED X ARE CRITICAL AND MUST BE CHECKED IN ACCORDANCE WITH QUALITY DOC. QI-02A

Leo	5	27.06.14	A431
Allan	4	06.10.08	A166
Allan	3	04.07.09	A141
Allan	2	02.07.08	A139
Allan	1	18.09.06	-

NAME	ISS.	DATE	C/NOTE
APPROVED:		B.Lim	
CHECKED:		D.P	
DRAWN:		Leo	
CUSTOMER REF.:			
ASSEMBLY DRG:			

NOTES:

1. 10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE ± 0.20
2. CARRIER CAMBER IS WITHIN 1 mm IN 250 mm
3. MATERIAL: TRANSPARENT CONDUCTIVE POLYSTYRENE ALLOY.(UP-5000)
4. ALL DIMENSIONS MEET EIA-481-C REQUIREMENTS
5. THICKNESS: 0.35 ± 0.05 mm
6. COMPONENT LOAD PER 19" REEL: 1500 PCS

OBSOLETE

HARWIN

HARWIN USA TEL: 603 893 5376 FAX: 603 893 5396 mis@harwin.com	HARWIN Europe (UK) TEL: 023 9231 4545 FAX: 023 9231 4590 mis@harwin.co.uk	HARWIN Asia TEL: +65 6 779 4909 FAX: +65 6 779 3868 mis@harwin.com.sg
--	--	--

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X.X = ± 0.25 mm
X.XX = ± 0.15 mm
ANGLES = $\pm 5^\circ$
UNLESS STATED

MATERIAL:	SEE NOTES
FINISH:	SEE NOTES
S/AREA:	mm?

TITLE:	WIRE TO BOARD, WAFER, PITCH 1.25MM, RIGHT ANGLE. SMT TYPE, ASSEMBLY
DRAWING NUMBER:	M30-401 XX 46R
SHT	2
OF	2