


5.0 x 3.0 x 0.5 (mm) ISM 433 MHz Ceramic Chip Antenna (C4501)

Engineering Specification

1. Product Number

H 2 U 6 4 U 1 H 2 J 0 1 0 0



2. Features

- *Stable and reliable in performances
- *Low profile, compact size
- *RoHS 2.0 compliance
- *SMT processes compatible
- *AEC-Q200 compliant

3. Applications

- *ISM 433 band
- *Smart meters
- *Wireless alarm and security system
- *Industrial monitoring and control
- *IOT applications
- *LPD433

4. Description

Unictron's C4501 ceramic chip antenna is designed for ISM 433 MHz bands applications, covering frequencies 433.05 ~ 434.79 MHz. Fabricated with proprietary design and processes, C4501 shows excellent performance and is fully compatible with SMT processes which can decrease the assembly cost and improve device's quality and consistency.



詠業科技股份有限公司
Unictron Technologies Corporation
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip Antenna (C4501) Engineering Specification

DOCUMENT NO.

H2U64U1H2J0100

REV. D

5. Layout Guide & Electrical Specifications


5-1. Layout Guide (unit : mm)

Solder Land Pattern:


The solder land pattern (gray marking areas) is shown below. Recommendation on matching circuit will be provided according to customer's installation conditions.

With 150 x 100 mm² Evaluation Board

Grounding pin
Signal input



Top View




Bottom View


Transmission Line with 50Ω Impedance Characteristic

With 80 x 40 mm² Evaluation Board

Grounding pin
Signal input



Top View



Bottom View

Transmission Line with 50Ω Impedance Characteristic

Unictron
Technologies Corp.

2020-07-07

Document
Control Center



詠業科技股份有限公司
Unictron Technologies Corporation
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip Antenna (C4501) Engineering Specification

DOCUMENT NO.

H2U64U1H2J0100

REV.
D

5-2. Electrical Specifications (Evaluation Board Dimensions:150 x 100 mm²)


5-2-1. Electrical Table

Characteristics		Specifications	Unit
Outline Dimensions		5.0 x 3.0 x 0.5	mm
Ground Plane Dimensions		150 x 100	mm
Working Frequency		433.05 ~ 434.79	MHz
VSWR (@ center frequency)*		2 Max.	
Characteristic Impedance		50	Ω
Polarization		Linear Polarization	
Peak Gain	(@ 433 MHz)	0.2 (typical)**	dBi
Efficiency		62 (typical)**	%


*Center frequency means the frequency with the lowest value in return loss of the chip antenna on the evaluation board.

**A Typical value is for reference only, not guaranteed.

5-2-2. Return Loss & VSWR Return Loss (S₁₁)



VSWR (S₁₁)



詠業科技股份有限公司
Unictron Technologies Corporation
Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by :Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip
Antenna (C4501) Engineering Specification

DOCUMENT
NO.

H2U64U1H2J0100

REV.
D

5-3. Electrical Specifications (Evaluation Board Dimensions: 80 x 40 mm²)

5-3-1. Electrical Table


Characteristics		Specifications	Unit
Ground Plane Dimensions		80 x 40	mm
Working Frequency		433.05 ~ 434.79	MHz
VSWR (@ center frequency)*		2 Max.	
Characteristic Impedance		50	Ω
Polarization		Linear Polarization	
Peak Gain	(@ 433 MHz)	-7.3 (typical)**	dBi
Efficiency		12 (typical)**	%

*Center frequency means the frequency with the lowest value in return loss of the chip antenna on the evaluation board.


**A Typical value is for reference only, not guaranteed.

5-3-2. Return Loss & VSWR

Return Loss (S₁₁)



VSWR (S₁₁)



詠業科技股份有限公司
Unictron Technologies Corporation
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip Antenna (C4501) Engineering Specification


DOCUMENT NO.

H2U64U1H2J0100

REV.
D

6. Outline Dimensions of Antenna & Evaluation Board (unit: mm)


6-1. Antenna Dimensions



NOTE:

1. All materials are RoHS compliant.
2. "A~C" Critical Dimensions.
3. "()" Reference Dimensions.

PIN Definitions



Item	PIN 1	PIN 2	PIN 3
Terminal	Signal	Tuning / Ground	Soldering Pad

2020-07-07

Document Control Center



詠業科技股份有限公司
Unictron Technologies Corporation
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip Antenna (C4501) Engineering Specification



DOCUMENT NO.

H2U64U1H2J0100

REV.

D

6-2. Evaluation Board with Antenna



Unit : mm

Unictron
Technologies Corp.

2020-07-07

Document
Control Center



詠業科技股份有限公司
Unictron Technologies Corporation
Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip
Antenna (C4501) Engineering Specification

DOCUMENT
NO.

H2U64U1H2J0100





REV.

D

7. 3D Radiation Gain Pattern

7-1. On 150 x 100 mm² Evaluation Board

7-1-1. 3D Radiation Gain Pattern @ 433 MHz (unit: dBi)



Unictron
Technologies Corp.
2020-07-07
Document
Control Center



詠業科技股份有限公司
Unictron Technologies Corporation
Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip Antenna (C4501) Engineering Specification

DOCUMENT NO.


H2U64U1H2J0100

REV.
D

7-1-2. 3D Efficiency Table

Frequency (MHz)	428	429	430	431	432	433	434	435	436	437	438
Efficiency (dB)	-4.4	-3.5	-2.9	-2.5	-2.2	-2.0	-2.1	-2.4	-3.1	-3.9	-4.5
Efficiency (%)	36.1	44.6	51.6	56.6	60.3	62.8	62.4	57.2	49.0	41.2	35.3
Peak Gain (dBi)	-2.0	-1.1	-0.5	-0.1	0.1	0.2	0.1	-0.3	-1.0	-1.7	-2.4

7-1-3. 3D Efficiency vs. Frequency



詠業科技股份有限公司
Unictron Technologies Corporation
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip Antenna (C4501) Engineering Specification





DOCUMENT NO.

H2U64U1H2J0100

REV.
D

7-2. On 80 x 40 mm² Evaluation Board

7-2-1. 3D Radiation Gain Pattern @ 433 MHz (unit: dBi)



Unictron
Technologies Corp.
2020-07-07
Document
Control Center



詠業科技股份有限公司
Unictron Technologies Corporation
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip Antenna (C4501) Engineering Specification

DOCUMENT NO.


H2U64U1H2J0100

REV.
D

7-2-2. 3D Efficiency Table

Frequency (MHz)	428	429	430	431	432	433	434	435	436	437	438
Efficiency (dB)	-16.7	-15.1	-13.3	-11.5	-9.9	-9.1	-9.5	-10.8	-12.3	-14.0	-15.6
Efficiency (%)	2.2	3.1	4.7	7.1	10.3	12.4	11.2	8.4	5.9	4.0	2.7
Peak Gain (dBi)	-15.2	-13.6	-11.7	-9.9	-8.2	-7.3	-7.7	-8.9	-10.4	-12.0	-13.6

7-2-3. 3D Efficiency vs. Frequency



詠業科技股份有限公司
Unictron Technologies Corporation
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip Antenna (C4501) Engineering Specification


DOCUMENT NO.

H2U64U1H2J0100

REV.
D

8. Soldering Conditions

Typical Soldering Profile for Lead-free Process



*Recommended solder paste alloy: SAC305 (Sn96.5 /Ag3 /Cu0.5) Lead Free solder paste.

9. Reminders for users of Unictron's C4501 ceramic chip antennas

- 9-1. This chip antenna is made of ceramic materials which is relatively more rigid and brittle compared to circuit board materials. Furthermore, the length of this antenna is quite long. Bending of circuit board at the locations where chip antenna is mounted may cause the cracking of solder joints or antenna itself.
- 9-2. Punching/cutting of the break-off tab of PCB panel may cause severe bending of the circuit board which may result in cracking of solder joints or chip antenna itself. Therefore break-off tab shall be located away from the installation site of chip antenna.
- 9-3. Be cautious when ultrasonic welding process needs to be used near the locations where chip antennas are installed. Strong ultrasonic vibration may cause the cracking of chip antenna solder joints.



詠業科技股份有限公司
Unictron Technologies Corporation
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip Antenna (C4501) Engineering Specification

DOCUMENT NO.


H2U64U1H2J0100

REV.
D

10. Packing

- (1) Quantity/Reel: 6000 pcs/Reel
- (2) Plastic tape:

a. Tape Drawing



b. Tape Dimensions (unit: mm)

Feature	Specifications	Tolerances
W	12.00	±0.30
P	8.00	±0.10
E	1.75	±0.10
F	5.50	±0.10
P2	2.00	±0.10
D	1.20	+0.10 -0.00
P0	4.00	±0.10
10P0	40.00	±0.20

11. Operating & Storage Conditions

11-1. Operating

- (1) Maximum Input Power: 2 W
- (2) Operating Temperature: -40°C to 85°C
- (3) Relative Humidity: 10% to 70%

11-2. Storage (sealed)

- (1) Storage Temperature: -5°C to 40°C
- (2) Relative Humidity: 20% to 70%
- (3) Shelf Life: 1 year

11-3. Storage (unsealed)

Meet the criteria of J-STD-033 MSL2a

11-4. Storage (After mounted on customer's PCB with SMT process)

- (1) Storage Temperature: -40°C to 85°C
- (2) Relative Humidity: 10% to 70%



詠業科技股份有限公司
Unictron Technologies Corporation
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip Antenna (C4501) Engineering Specification

DOCUMENT NO.

H2U64U1H2J0100

REV.
D

12. Notice

(1) Installation Guide:

Please refer to Unictron's application note "General guidelines for the installation of Unictron's chip antennas" for further information.

(2) All specifications are subject to change without notice.



詠業科技股份有限公司
Unictron Technologies Corporation
Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by :Jane

Designed by : George

Checked by : Mike

Approved by : Herbert

TITLE : 5.0 x 3.0 x 0.5 (mm) ISM 433MHz Ceramic Chip Antenna (C4501) Engineering Specification

DOCUMENT NO.

H2U64U1H2J0100

REV.
D