GlobTek, Inc. www.globtek.com	Drawing Title: USB-C (USB TYPE-C) USB 3.2 Gen 2 (USB 3.1 Gen 2, Superspeed + (USB 3.1)) Receptacle Connector 6 Position Waterproof IPX7 Surface Mount, Right Angle; Through Hole, 450-01290404(R)		
186 Veterans Drive,	Model No. Connector		
Northvale, NJ 07647			
Tel. (201) 784-1000	Part No./Ordering No. JACK-USBC-061SMT-4BVC11	Rev A	
Fax (201) 784-0111			

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at http://www.globtek.com/iso-certificates/

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (http://en.globtek.com/terms-and-conditions/).

Prop 65 Statement:https://en.globtek.com/prop-65-statement.pdf

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.

Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing. A delay in receipt of this form will delay delivery schedule.

Company Name:	Customer P/N:
Quote Number:	Date:
Authorized Representative Name:	Authorized Representative Signature:

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2022 - 2023 guest /08/12/2023 4:13:52 AM CLONED FROM JACK-USBC-243SMT-3BVC84

	Drawing Title: USB-C (USB TYPE-C) USB 3.2 Gen 2 (USB 3.1 Gen 2, Superspeed + (USB 3.1)) Receptacle Connector 6 Position Waterproof IPX7 Surface More Right Angle; Through Hole, 450-01290404(R)			
U	Model No. Connector			
Northvale, NJ 07647				
Tel. (201) 784-1000	Part No./Ordering No. JACK-USBC-061SMT-4BVC11	Rev A		
Fax (201) 784-0111				

D CAD FILE: ttps://www.globt	nitial release	QA		08/03/2022	QA
ttps://www.globt					
	tek.com/file/dl/jack-usbc-061sr	mt-4bvc11_asm.stp			
			(
RoHS/RoHS3 De REACH Declarat		https://www.globtek.c			
Conflict Minerals		https://www.globtek.c			
Prop 65 Stateme		https://en.globtek.cor			
	sed on 3rd party testing and c				V rating before ordering
	0.98 (0.039) 45 48.35 (0.329) ^{1,0,05} 45 49 45 49 45 49 45 49 45 49 40 40 40 40 40 40 40 40 40 40	A12 2.60 (0.102)	4'0.50 (0.020) 8.64 (0.340) 2.30 (0 NDED P.C.8 LAYOUT UNSPECIFIED ±0.05mm 3.20 (0.126) 0.90 (0.035) 0 (0.031)		
	B12 B9 B9 B5 A5 A5 A9 A12 A12 S50 [0.217]	VBUS 0.0000 i CC2 0.0000 i CC1 0.0000	SBC-061SMT-4BVC	11	

WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2022 - 2023 guest /08/12/2023 4:13:52 AM CLONED FROM JACK-USBC-243SMT-3BVC84

GlobTek, Inc. www.globtek.com	Drawing Title: USB-C (USB TYPE-C) USB 3.2 Gen 2 (USB 3.1 Gen 2, Superspeed + (USB 3.1)) Receptacle Connector 6 Position Waterproof IPX7 Surface Mount, Right Angle; Through Hole, 450-01290404(R)		
186 Veterans Drive,	Model No. Connector		
Northvale, NJ 07647			
Tel. (201) 784-1000	Part No./Ordering No. JACK-USBC-061SMT-4BVC11	Rev A	
Fax (201) 784-0111			

NOTES:

1.MATERIAL: MOLDING: LCP UL94V-0 CONTACT: COPPER ALLOY.

2. Finished: contact area: plating Au 0.8u",
solder tail: plating Au 0.8u", all plating Ni 40u"
SHELL: SUS201-1/2HT=0.30+0.03mm
50U' NICKEL PLATING OVER ALL.

3.MECHANICAL: INSERTION: 5~20N. EXTRACTION: 8~20N AFTER TEST. DURABILITY: 8000 CYCLES


4.ELECTRICAL: CURRENT: 5A FOR VBUS: 1.25A FOR GND PIN 0.25A FOR OTHER VOLTAGE: 20 V MAX WITHSTANDING VOLTAGE: 100V AC R.M.S. CONTACT RESISTANCE: 40mΩ MAX. INSULATION RESISTANCE: 100MΩ MIN.

5.ENVIRONMENTAL TEMPERATURE RATING: -25°C ~ +85°C

Temperature Life, Vibration, Cyclic Temperature and Humidity, Thermal Shock, Mixed Flowing Gas and etc.: <u>https://www.globtek.com/pdf/ENVIRONMENTAL.pdf</u>

PROPRIETARY INFORMATION
PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN
WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2022 - 2023
guest /08/12/2023 4:13:52 AM CLONED FROM JACK-USBC-243SMT-3BVC84
Page 3 of 6

GlobTek, Inc. www.globtek.com	Pight Angle: Through Hole, 450, 01200404/P)		
186 Veterans Drive,	Model No. Connector		
Northvale, NJ 07647			
Tel. (201) 784-1000	Part No./Ordering No. JACK-USBC-061SMT-4BVC11	Rev A	
Fax (201) 784-0111			



guest /08/12/2023 4:13:52 AM CLONED FROM JACK-USBC-243SMT-3BVC84

GlobTek, Inc. www.globtek.com	Drawing Title: USB-C (USB TYPE-C) USB 3.2 Gen 2 (USB 3.1 Gen 2, Superspeed + (USB 3.1)) Receptacle Connector 6 Position Waterproof IPA Right Angle; Through Hole, 450-01290404(R)	(7 Surface Mount,
186 Veterans Drive,	Model No. Connector	
Northvale, NJ 07647		
Tel. (201) 784-1000	Part No./Ordering No. JACK-USBC-061SMT-4BVC11	Rev A
Fax (201) 784-0111		

RIETARY INFORMATION ETARY OF GLOBTEK, INC. ANY I 3 BY GLOBTEK, INC. © GlobTek,	REPRODUCTION, DISCLOSURE OR L	JSE OF THIS DRAWING, IN WH	HOLE OR IN PART, IS HEREB	PROHIBITED EXCEPT AS SPECIFIED	DIN Page 5

GlobTek, Inc. www.globtek.com Braking Title: USB-C (USB TYPE-C) USB 3.2 Gen 2 (USB 3.1 Gen 2, Superspeed + (USB 3.1)) Receptacle Connector 6 Position Waterproof Right Angle; Through Hole, 450-01290404(R)			
186 Veterans Drive,	Model No. Connector		
Northvale, NJ 07647			
Tel. (201) 784-1000	Part No./Ordering No. JACK-USBC-061SMT-4BVC11	Rev A	
Fax (201) 784-0111			

PACKAGING

Packing Spec P/N:	
Box Qty:	5000
Gift Box Size (mm):	
Gift Box Color:	White
Master Carton Size (mm):	340 x 340 x 220
Master Carton Cubic Volume (m	³): 0.03
Master GW (Kg):	8.0 kg
wt Ea. (Kg):	0.00 kg
wt Ea. (Kg):	0.00 kg
LABEL SPECS: ,	

PACK SPEC: