9080GCB70

Circuit protector, Linergy, thermal magnetic overcurrent, track mount, 7.0A, 250 VAC / 65 **VDC**



Main

Range of Product	9080GCB
Product or Component Type	Circuit Protector
Trip Unit Type	Thermal-magnetic
Electrical Connection	Box lugs

Complementary

o o mpromornary	
Protection Type	Overcurrent
Contact operation	Trip-free
Device Application	Industrial Application
Line Rated Current	7 A
Number of Poles	1P
Votlage Rating	250 V AC 65 V DC
Wire Size	AWG 16AWG 10 copper
Wire stripping length	0.5 in (12.70 mm)
Terminal Tightening Torque	Control circuit 7 lbf.in (0.79 N.m) cage type connector
Terminal Rating	Factory wiring only
Operating Temperature	-22140 °F (-3060 °C)
Calibration Temperature	70 °F (21 °C)
Mounting Support	9080GH track 35 mm DIN rail
Height	3.45 in (87.63 mm)
Width	3.15 in (80.01 mm)
Depth	0.5 in (12.70 mm)

Environment

Product Certifications	CE UL recognized E233026 CCN QVNU2 CSA file 025490 class 3211 07
Standards	UL 1077 CSA C22.2 No 235 DIN 57470

Ordering and shipping details

Category	21703-9080 GCB	
Discount Schedule	CP5	
GTIN	785901000945	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.56 oz (72.575 g)	
Returnability	Yes	
Country of origin	DE	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.10 in (2.794 cm)	
Package 1 width	3.30 in (8.382 cm)	
Package 1 Length	3.70 in (9.398 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to
	www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

	,	
Warranty	18 months	