

Cable gland - G-ESSWU-M40-L66L-NTES-S - 1411097

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Nickel-plated brass, Application: Ex, External cable diameter 27.9 mm ... 40.4 mm, Shielding: No, Connecting thread: M40, Color: silver

Product Features

-
- Armor connected via PE cone



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	680.0 g
Custom tariff number	74199990
Country of origin	United Kingdom

Technical data

Dimensions

Length	93 mm
Wrench size, union nut	55 mm
Wrench size, support	55 mm
Hexagon angular dimension GRP	60.5 mm
Length of the connecting thread	15 mm
External cable diameter	27.9 mm ... 40.4 mm
Armor connection method	Cone
Armor thickness	1.6 mm ... 2 mm (Stepped cone side (SWA/...))
	0 mm ... 1.2 mm (Grooved cone side (STA/...))
Cable diameter without armor	32.2 mm (Filler beneath the armor)

Cable gland - G-ESSWU-M40-L66L-NTES-S - 1411097

Technical data

Ambient conditions

Degree of protection	IP66 (using the corresponding A-SEW-...P-W flat gasket)
	IP67 (using the corresponding A-SEW-...P-W flat gasket)
	IP68 (using the corresponding A-SEW-...P-W flat gasket)
Ambient temperature (operation)	-60 °C ... 130 °C

General

Cable gland material	Nickel-plated brass
Seal material	EPDM
Cable seal material	EPDM
O-ring material	Viton
Thread type on connection side	M40
Color	silver
Standards/specifications	EN 60079-0, -7, -15, -31
	IEC 60079-0, -7, -15, -31
	EN 50262
	BS 6121: Part 1:1989
	IEC 62444
Manufacturer	CMP
Manufacturer Designation	C2K, thread size 40

Standards and Regulations

Standards/regulations	EN 60079-0, -7, -15, -31
	IEC 60079-0, -7, -15, -31
	EN 50262
	BS 6121: Part 1:1989
ATEX	Sira 13ATEX1070X
	Sira 13ATEX4076X
	Ex II 2G, II 1D, Ex e IIC Gb, Ex ta IIIC Da, Ex II 3G Ex nR IIC Gc
IECEX	IECEX SIR 13.0025X
	Ex e IIC Gb, Ex nR IIC Gc, Ex ta IIIC Da

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109

Cable gland - G-ESSWU-M40-L66L-NTES-S - 1411097

Classifications

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Drawings

Dimensional drawing

