



**TECHNICAL**

AGENCY APPROVAL:	cULus
RATED SUPPLY VOLTAGE:	240VAC
RATED CURRENT:	UP TO 20 AMPS
RESET TYPE:	MANUAL
OPERATING FREQUENCY:	60 Hz
TYPE:	CLASS A
GROUND TRIP CURRENT:	4-6 mA
OVERLOAD CURRENT:	120 AMP
INSULATION VOLTAGE:	1,500 VRMS - 1 MINUTE
ENDURANCE OPERATIONS:	3000 OPERATIONS
ENCLOSURE:	NEMA 3R

MATERIAL NO.	PART NO.	OUTPUT CORD LENGTH	VOLTAGE
1301530203	30-0905	9.00 IN. ± 0.5"	240VAC
1301530204	30-0906	5.0 FT. ± 1.0"	240VAC
1301530205	30-0907	24.0 FT. +2.0"/-0.0"	240VAC

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
FUNCTIONAL SYMBOLS		DIMENSION UNITS		SCALE		CURRENT REV DESC: UPDATED GFCI BODY.			
$\nabla_A = 0$		INCH		NTS		<p>EC NO: 730358</p> <p>DRWN: PPURSUTANDEL 2022/10/19</p> <p>CHK'D: DNGUYENG2 2023/02/16</p> <p>APPR: HKNEELAND 2023/02/21</p> <p>INITIAL REVISION:</p> <p>DRWN: PPURSUTANDEL 2021/12/13</p> <p>APPR: HKNEELAND 2022/01/20</p>			
$\nabla_C = 0$		GENERAL TOLERANCES (UNLESS SPECIFIED)							
$\nabla_P = 0$		ANGULAR TOL ± °							
DIVISIONAL SYMBOLS		4 PLACES ±							
		3 PLACES ±							
		2 PLACES ±							
		1 PLACE ±							
		0 PLACES ±							
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES		DOCUMENT NUMBER	
				C-SIZE		130153		1301530203	
								DOC TYPE   DOC PART   REVISION	
								PSD   000   B	
								MATERIAL NUMBER   CUSTOMER   SHEET NUMBER	
								SEE TABLE   GENERAL MARKET   1 OF 1	