

**1 of 6 pages**

This Dielectric Strength Tester is ideal for testing control panels, small transformers, electrical motors, appliances, light fixtures, similar equipment.



**Portable Dielectric Strength Tester (HI POT)  
MODEL AV-25DV-5-SD-01**

<b>INPUT</b>	120 V 60 Hz 3 A
<b>OUTPUT</b>	Adjustable: 0-2500 V ac @ 5 mA
<b>TRANSFORMER</b>	Rated 300 VA Short Duty Cycle
<b>VOLTMETER</b>	DPM 0-2500 V ac @ Accuracy: $\pm 2\%$ of full scale
<b>TRIP CURRENT</b>	Fixed @ 5 mA $\pm 5\%$
<b>INDICATORS</b>	4 Lights (Power-on, High-Voltage-on, Fault and Line Fault)
<b>CONTROLS</b>	One on/off switch, one fuse, one reset push-button, one high-voltage adjust-knob and safety device for faulty power outlet.
<b>LEADS</b>	One input Line-Cord 2 meters (6 ft) long, one ground lead c/w a clip and one high-voltage lead c/w high-voltage retractable probe. Each 1 meter (3 ft) long.
<b>SIZE</b>	30W x 25D x 20H cm (12W x 10D x 8 inches)
<b>WEIGHT</b>	5 kg (11 Lb)

## 2 of 6 pages

This Dielectric Strength Tester is ideal for testing: control panels, small transformers, electrical motors, appliances light fixtures and similar equipment.



**Portable dielectric strength tester (Hi Pot)  
MODEL AV-25DV-10-SD-01**

<b>INPUT</b>	120 V 60 Hz
<b>OUTPUT</b>	Adjustable: 0-2500 V ac @ 10 mA
<b>TRANSFORMER</b>	Rated 300 VA Short Duty Cycle
<b>VOLTMETER</b>	Digital 0-2500 V ac Accuracy $\pm 2\%$ of full scale
<b>TRIP CURRENT</b>	Fixed @ 10 mA $\pm 5\%$
<b>INDICATORS</b>	4 lights (power on, high-voltage-on, fault and line-fault)
<b>CONTROL</b>	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
<b>LEADS</b>	One input line-cord 2 meters (6 ft) long, one ground lead c/w a clip and one high-voltage lead c/w a clip. Each is 1 meter (3ft) long.
<b>SIZE</b>	30W x 25D x 20H cm (12W x 10D x 8H inches)
<b>WEIGHT</b>	5 kg (11Lb)

### 3 of 6 pages

This Dielectric Strength Tester is ideal for testing control panels, transformers, electrical motors, appliances, light fixtures and similar equipment.



**Portable Dielectric Strength Tester (Hi Pot)  
MODEL DV-25DV-5-SD-01**

<b>INPUT</b>	120 V 60 Hz
<b>OUTPUT</b>	Adjustable: 0-2500 V dc @ 5 mA
<b>TRANSFORMER</b>	Rated 300 VA Short Duty Cycle
<b>VOLTMETER</b>	Digital 0-2500 V dc Accuracy: $\pm 2\%$ of full scale
<b>TRIP CURRENT</b>	Fixed @ 5 mA $\pm 5\%$
<b>INDICATORS</b>	4 Lights (power-on, high-voltage-on, fault and line fault)
<b>CONTROLS</b>	One on/off switch, one fuse, one reset push-button, one high-voltage adjust-knob and safety device for faulty power outlet.
<b>LEADS</b>	One input line-cord 2 meters (6 ft) long, one ground lead c/w a clip and one high-voltage lead c/w clip.
<b>SIZE</b>	30W x 25D x 20H cm (12W x 10D x 8 inches)
<b>WEIGHT</b>	5 kg (11 lb)

## 4 of 6 pages

This Dielectric Strength Tester is ideal for testing control panels, small transformers, electrical motors, appliances, light fixtures and similar equipment.



**Portable Dielectric Strength Tester (Hi Pot)  
MODEL DV-25DV-10-SD-01**

<b>INPUT</b>	120 V 60 Hz
<b>OUTPUT</b>	Adjustable: 0-2500 V dc @ 10 mA
<b>TRANSFORMER</b>	Rated 300 VA Short Duty Cycle
<b>VOLTMETER</b>	Digital 0-2500 V dc Accuracy: $\pm 2\%$ of full scale
<b>TRIP CURRENT</b>	Fixed @ 10 mA $\pm 5\%$
<b>INDICATORS</b>	4 lights (power-on, high-voltage-on, fault and line-fault)
<b>CONTROLS</b>	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power outlet.
<b>LEADS</b>	One input line-cord 2 meters (6 ft) long, one ground lead c/w a clip and one high-voltage lead c/w a clip. Each is 1 meter (3 ft) long
<b>SIZE</b>	30W x 25D x 20H cm (12W x 10D x 8H inches)
<b>WEIGHT</b>	5 kg (11 Lb)

**5 Of 6 pages**

This bench type Dielectric Strength Tester is ideal for testing control panels, transformers, electrical motors, appliances, light fixtures, electrical cables and similar equipment.



**DIELECTRIC STRENGTH TESTER (Hi Pot)  
MODEL AV-25DV-5**

<b>INPUT</b>	120 V 60 Hz
<b>OUTPUT</b>	Adjustable: 0-2500 V ac @ 5 mA
<b>TRANSFORMER</b>	Rated 500 VA Short Duty Cycle
<b>VOLTMETER</b>	Digital 0-2500 V ac Accuracy: $\pm 2\%$ of full scale
<b>TRIP CURRENT</b>	Fixed @ 10 mA $\pm 5\%$
<b>INDICATORS</b>	4 lights (power-on, high-voltage-on, fault and line-fault)
<b>CONTROLS</b>	One on/off switch, one fuse, one reset push-button, one high-voltage adjust-knob and safety device for faulty power-outlet.
<b>LEADS</b>	One input line-cord, one ground lead c/w a clip and one high-voltage lead c/w a retractable probe. Each is 2 meters (6 ft) long.
<b>SIZE</b>	30W x 25D x 18H cm (12W x 10D x 7H inches)
<b>WEIGHT</b>	9.5 kg (21 Lb)

## 6 of 6 pages

This Dielectric Strength Tester is ideal for testing control panels, transformers, electrical motors, appliances, light fixtures electrical cables and similar equipment.



**DIELECTRIC STRENGTH TESTER (Hi POT)  
MODEL DV-25DV-5**

<b>INPUT</b>	120 V 60 Hz
<b>OUTPUT</b>	Adjustable: 0-2500 V dc @ 5mA
<b>TRANSFORMER</b>	Rated 500 VA Short Duty Cycle
<b>VOLTMETER</b>	Digital 0-2500 V dc Accuracy: $\pm 2\%$ of full scale
<b>TRIP CURRENT</b>	Fixed @ 5 mA $\pm 5\%$
<b>INDICATORS</b>	4 lights (power-on, high-voltage-on, fault and line-fault)
<b>CONTROLS</b>	One on/off switch, one fuse, one reset push-button, one high-voltage adjust-knob and safety device for faulty power-outlet.
<b>LEADS</b>	One input line-cord 2 meters (6 ft) long, one ground lead c/w a clip and one high-voltage lead c/w a retractable probe. Each one of them is 2 meters (6 ft) long.
<b>SIZE</b>	30W x 25D x 18H cm (12W x 10D x 7H inches)
<b>WEIGHT</b>	9.5 kg (21 Lb)